

North Dakota Broadband Mapping Methodology Report

Submitted To:

Travis Durick
Broadband Technology Manager
Information Technology Department
State of North Dakota

Submitted By:

Fred Gifford
Tetra Tech EC Inc.
and
Ken Wall
Geodata Services Inc.
September 21, 2012

Contents

Executive Summary.....	1
Provider Summary	1
Data Sources	2
Broadband Coverage.....	2
Providers Submitting FCC Form 477 Reports or Similar Format.....	5
Providers Submitting Census Block Coverage.....	9
Providers Submitting Coverage Data	11
Providers Submitting Customer Locations.....	14
Providers Submitting Other Levels of Coarse Geographic Submission	16
Cable Modem Geoprocessing Model.....	16
DSL Geoprocessing Model	17
2000 TO 2010 Census Block Conversion.....	18
Road Segment Geoprocessing Change	18
Wireless Coverage.....	20
Providers Submitting FCC Form 477 Report or Similar Format	21
Providers Submitting Census Block Coverage.....	21
Providers Submitting Actual Coverage Maps	22
Providers Submitting Other Levels of Coarse Geographic Submission	22
Satellite	23
Community Anchor Institutions.....	23
Middle Mile	25
Speed Test Data Processing	26
Reliability, Validity and Completeness.....	30

Reliability Codes.....	30
Validity Codes.....	32
Infrastructure Validity Codes	32
Final Technology of Transmission Validity Codes	32
Quality Assurance Testing.....	33
Appendix A.....	37

Executive Summary

The following report describes methods and issues related to the October 1, 2012 deliverables to NTIA for Broadband Mapping in North Dakota. This data submission is compliant with all guidance and specifications provided by NTIA. As per NTIA guidance we are using current versions of the Broadband data model and the validation script.

North Dakota has developed a robust operational data model, components of which are described in this report, to support our broadband mapping efforts. We feel our operational model can support any reasonable modifications to NTIA requirements. Since this deliverable format is derived from our operational data model, we anticipate some modifications will be required. We are able to take best practices recommendations from the NTIA and incorporate those into the final deliverable without major modifications of our work flow and operating rules.

Our mapping process started with infrastructure points (central offices, remote terminals, wireless towers and antenna locations, middle mile and backhaul), cable franchise areas, and anchor institution addresses. Those served an important role, especially with providers who have not actively participated in coverage mapping and those supplying broadband coverage for large generalized areas and larger geographic census units such as census tracts. When providers have not supplied detailed information of their service areas that can be mapped at the census block level, coverage models were derived dynamically from this infrastructure based on geoprocessing techniques specific to each broadband technology. Examples of geoprocessing techniques include using infrastructure points in conjunction with the road network to predict the area served for DSL coverage. For all providers of wired broadband services, those have all been completed and remain static unless a provider chooses to participate with more detailed coverage mapping at a level of geography at or smaller than a census block.

We developed a system to quantify “validated” data for the purpose of determining what was suitable for delivery to NTIA. The operational data model maintained reliability and validity codes. As more data is obtained from providers in maintenance updates, the validity and reliability of infrastructure points has diminished, though they remain the only basis we have for non-participating broadband providers.

Provider Summary

Through extensive research we identified a master list of 173 potential providers in North Dakota with 52 companies identified as actual broadband providers. The North Dakota

Broadband map includes 50 broadband providers. The full list of the potential providers researched but subsequently identified as not providing broadband service is included in Appendix A.

Data Sources

In the first rounds of broadband mapping, provider presence maps were developed for central office locations and incumbent local exchange carrier locations for all assumed providers in the state. These were identified through a commercial spatial database purchased from GeoTel Inc., and supplemented by other public data sources such as the State's Public Service Commission and DSLReports.com. These were intended to be "talking maps" and general intelligence on where providers have infrastructure for subsequent phone and written communications with providers. These maps were compared to counties served by provider in the state's telecommunications association directory.

Web site research, review of materials submitted to the state by providers, and public websites, such as the FCC were researched for each provider.

New providers are contacted to request data when a significant number of speed tests are recorded, or when we learn of their presence through ancillary sources. Providers that contact us directly and submit data are also included.

Broadband Coverage


Data submitted by broadband providers was accepted as is and was mapped in complete form when provided as a broadband coverage at the same scale or larger scale than the census block level. Provider coverage submitted at a coarser geographic scale (e.g., census tracts, counties, zipcodes) was supplemented with public data, independent measurements and GIS modeling techniques. When provider submitted data appeared to be exaggerated or providers did not participate in the broadband mapping process, independent measurements and other data sources (e.g., state GIS framework structure locations, speed tests, survey results, website data and infrastructure) were used to override or supplement the provider data.

Broadband providers that chose to submit data did so in a wide variety of formats, levels of completeness, and at varying geographic scales including: narrative descriptions, analog and digital coverage maps, CAD files, GIS shapefiles and geodatabases, KMZ and KML files, FCC 477 reports, and data spreadsheets. All data formats were accommodated and processed whenever possible.

If data was submitted by a provider in a format that did not allow mapping at the census block level of geography, providers were sent standardized maps that included census blocks and a data spreadsheet in an attempt to standardize the inputs and increase the geographic granularity of the provider data submission.

Although each provider had individual characteristics and nuances in their data submissions, several data patterns can be described generalizing the provider submissions.

Figure 1 Provider Submission Types and Workflow





Providers Submitting FCC Form 477 Reports or Similar Format

Broadband providers are required to submit FCC Form 477 reports twice a year to the FCC; recently 477 submissions have been done using a structured web site maintained by the FCC. The 477 reports require broadband providers to submit a list of census tracts with the number of subscribers based on maximum advertised downstream and upstream speed tiers. Several providers submitted their actual FCC 477 report or a modified version in analog or digital format.

Figure 2 FCC Form 477 Example

FCC Form 477 - Local Telephone Competition and Broadband Reporting Page 1 of 2

 Search | RSS | Updates | E-Filing |
Initiatives | Consumers |
Find People 

FCC Form 477 - Local Telephone Competition and Broadband Reporting
Form 477 [REDACTED] NO: 3060-0816

Form 477 Submission for FRN: 2477693, Company: Northwest Communications Cooperative, Inc., State: ND, Operations: ILEC, Data as of Dec 31, 2009

Census Tract Detail - Technologies except Terrestrial Mobile Wireless

If you reported broadband connections in Part I.A in a technology category other than Terrestrial Mobile Wireless, you must specify the technology category, identify the Census Tracts in this state in which you had connections in service using that technology, and, for each Census Tract, report the number of connections and the percentage residential in each relevant download/upload information transfer rate combination.

You can use the [Federal Financial Institutions Examination Council Geocoding System](#) to look up Census Tract numbers for street addresses.

Census Tract / Technology:
Technology of the connections: **Asymmetric xDSL**
Census Tract: State: ND County: Burke Census Tract: **9532.00**

DOWNLOAD INFORMATION TRANSFER RATE.

UPLOAD INFORMATION TRANSFER RATE:	Greater than 200 kbps and less than 768 kbps	Greater than or equal to 768 kbps and less than 1.5 mbps	Greater than or equal to 1.5 mbps and less than 3 mbps	Greater than or equal to 3 mbps and less than 6 mbps	Greater than or equal to 6 mbps and less than 10 mbps	Greater than or equal to 10 mbps and less than 25 mbps	Greater than or equal to 25 mbps and less than 100 mbps	Greater than or equal to 100 mbps
Less than or equal to 200 kbps Number of Connections: _____ Percentage Residential: _____	%	%	%	%	%	%	%	%
Greater than 200 kbps and less than 768 kbps Number of Connections: _____ Percentage Residential: _____	76	214						
Greater than or equal to 768 kbps and less than 1.5 mbps Number of Connections: _____ Percentage Residential: _____	%	91	86	%	%	%	%	%
Greater than or equal to 1.5 mbps and less than 3 mbps Number of Connections: _____ Percentage Residential: _____	%	%	%	%	%	%	%	%
Greater than or equal to 3 mbps and less than 6 mbps Number of Connections: _____ Percentage Residential: _____	%	%	%	%	%	%	%	%
Greater than or equal to 6 mbps and less than 10 mbps Number of Connections: _____ Percentage Residential: _____	%	%	%	%	%	%	%	%

https://specialreports.fcc.gov/wcb/Form477/Part_6_census.cfm 2/11/2010


How They Were Handled

FCC Form 477 reports were entered into a standardized format that included the census tract ID code, maximum advertised downstream and upstream speed tier code, and number of subscribers (when available). Since the FCC 477 reports requires providers to submit data for all speed tiers within a census tract, only the highest maximum advertised speed for any given census tract was entered into the standardized spreadsheet in order to be compliant with the definition of broadband service.

The spreadsheets were then joined to a census tract feature class template that included the attribute fields from the NTIA schema. The resulting feature class was a geographical representation of the FCC 477 report including the technology of transmission and speed information. This feature class was used in conjunction with validated infrastructure data (i.e., central offices and/or remote terminals) to run the DSL or Cable geoprocessing models respectively.


The resulting census block selection from the DSL or Cable model was displayed on a standardized review map and returned to the provider for confirmation.

Figure 3 Review Map Example



If additional edits were required the provider “marked-up” the review map(s) to indicate which census blocks should be added and/or removed. The provider submission was handled as a census block update (describe in the section below) from that point forward. In future updates from those providers FCC Form 477 data was not accepted and providers who originally submitted data in this format were asked to make edits to the review maps.

Figure 4 Provider's "Marked-Up" Map Example



Several providers did not respond to the original confirmation maps and their final submission represented the best modeled estimate of their coverage at the census block level for DSL and/or Cable technologies. Providers that submitted FCC 477 data for fiber to the end user or fixed wireless could not be mapped and were not included in the final broadband map unless they provided additional data at the census block level or equivalent coverage at a similar scale.


Providers Submitting Census Block Coverage

Census blocks submitted by providers representing their broadband coverage area come in a wide range of formats including: analog and digital maps, CAD files, GIS shapefiles and geodatabases, tabular lists, and spreadsheets.

Figure 5 Census Block Submission Example

Caledonia City Census Blocks
Blocks are indicated where ADSL
service is provided

Maximum Advertised download speed: 4
Maximum Advertised upload speed: 3
Typical download speed: 2
Typical upload speed: 2




How They Were Handled

All census block submittals were loaded into a census block feature class template that included all of the attribute fields from the current NTIA schema. Census 2010 geography was used as required by NTIA. Domain codes were entered in the appropriate attribute field for technology of transmission, maximum advertised downstream speed, and maximum advertised upstream speed. If a provider did not identify the technology of transmission for a given census block or blocks, they were contacted by phone or email in order to obtain this information. In instances where speed information was not included in the data submission providers were contacted

and asked to supply this data; in cases where the provider refused to supply either the downstream, upstream, or both speeds, and their advertised speeds were not available on their web site, the lowest domain code was entered in the applicable attribute field.

Standardized confirmation maps were created for each provider by type of technology and sent to the provider for review. Once processing was completed for a provider's census block submission, the census block feature class was run through an Esri geoprocessing model that performed several quality control-quality assurance tests and selected census blocks less than or equal to two square miles and road segments that intersected census blocks greater than two square miles and were appended to the appropriate NTIA transfer data model feature classes.


Figure 6 Census Block Geoprocessing Model



Providers Submitting Coverage Data

Provider submitted coverage data were differentiated from the other types of geographic data submissions coarser than a census block since they represented the full and explicit range of broadband coverage. Similar to the other types of data submissions, coverage data was also provided in a wide range for formats including: analog and digital maps, CAD files, GIS shapefiles and geodatabases. Coverage data was submitted by several providers or was available on several providers' websites.

Figure 7 Coverage Data Example



How They Were Handled


All coverage data was loaded into a coverage template feature class schema that included all of the attribute fields from the NTIA schema. The method of data loading was driven by the format in which it was received. Providers who supplied GIS shapefiles or feature classes could generally be loaded into the coverage template feature class schema using the simple data loader while CAD data had to be exported to GIS format prior to being loaded into the coverage template.

Coverage data supplied as digital or analog maps required georectification and digitizing prior to loading into the coverage template feature class. Domain codes were entered in the appropriate attribute field for technology of transmission, maximum advertised downstream speed, maximum advertised upstream speed, and spectrum. If a provider did not identify the technology of transmission for a given coverage area, they were contacted by phone or email in order to obtain this information.

When speed information was not included in the data submission, providers were contacted and asked to supply this data; in cases where the provider refused to supply either the downstream, upstream, or both speeds, the lowest domain code was entered in the applicable attribute field. If a provider did not specify the type and spectrum used for fixed wireless the default values for unlicensed were used.

Standardized confirmation maps were created for each provider by type of technology and sent to the provider for review. Once processing was completed for a provider's coverage submission, the data was run through an Esri geoprocessing model that performed several quality control-quality assurance tests and selected census blocks less than or equal to two square miles when the centroid of the census block was within the coverage area. Road segments that intersected with census blocks greater than two square miles were selected and then clipped to the coverage area in order to provide the most accurate representation based on the provided coverage. The selected census blocks and road segments were appended to the appropriate feature class in the NTIA data transfer model.

Figure 8 Coverage Geoprocessing Model




Providers Submitting Customer Locations

Providers that submitted customer locations typically fell into one of four categories. Several providers submitted customer locations in AutoCAD files, the points were exported to a shapefile and used to select all intersecting census blocks. Other providers submitted analog or digital maps that included customer locations, these images were georectified and census blocks were selected by an operator viewing the customer point images underlying the census blocks. Lists of customer addresses were also submitted. The data was loaded into a spreadsheet and geocoded using ESRI Business Analyst USA Geocoding engine. The geocoded points were treated identically to customer locations submitted in GIS or CAD format and used to select intersecting census blocks.

The resulting census blocks were added to confirmation maps and returned to the provider. If edits were necessary the provider indicated on the map which census blocks needed to be added and/or removed. The provider submission was handled as a census block update (described in the section above) moving forward. In subsequent updates subscriber address data was discouraged and providers who originally submitted data in this format were asked to make edits to the review maps.

Figure 9 Customer Addresses Geoprocessing Model



Providers Submitting Other Levels of Coarse Geographic Submission

This category had a wide range of submissions. The most common were telephone exchange areas or equivalent, wire centers, zip codes, counties or general references to towns or cities. These coarse geographic submissions were problematic because these areas were typically very large and lacked the detail of a defined coverage area resulting in over-exaggerated broadband coverage.

How They Were Handled

Operational rules established early in the project heavily scrutinized provider data that appeared to significantly over-represent broadband coverage and often resulted in a rejection of the submitted data. Providers who submitted coarse geographic levels of coverage data and infrastructure for DSL or cable modem service were initially that also were represented in the last point of aggregation infrastructure point file were sent estimated census block coverage maps and spreadsheets, and provided a second submission with finer level geography.

Providers submitting town locations for DSL or Cable were handled differently, and used as validation for central offices from the last point of aggregation table, and subsequently to run the DSL modeling routine or validate a cable or cable plus areas.

Cable Modem Geoprocessing Model

An ESRI geoprocessing model was created to generate coverage areas for Cable providers who did not submit census block or coverage data (i.e., census tract providers).

The most authoritative GIS layer available from the state with incorporated areas and city boundaries was used as a surrogate to model cable broadband coverage. Some towns that were not incorporated were also added. Municipalities and towns were sporadic in their digital update of these maps, since annexations and other boundary modifications were ongoing and difficult to maintain in real time updates. To compensate, likely areas contiguous to these city boundaries were added, labeled "Cable-Plus" in the operational data model. These additional polygons were determined using operator interpretation, road density, structures points from Info USA in Esri Business Analyst, speed test results, and in some instances NAIP imagery. In general areas were added that were immediately contiguous to existing city or town boundaries that represented likely areas where cable service existed. We were conservative in this approach and did not include populated areas near the cable plus boundaries unless they were directly contiguous to existing boundary areas.

Cable broadband providers primarily work under the structure of franchise agreements with municipalities. In the early rounds of broadband mapping updates, phone calls were made to

the largest cities in the state in order to obtain that respective city's cable franchise agreement. They were all either unknown or a text agreement without maps.

The full set of potential cable areas were then passed through validation sources to determine if cable was provided. This included public sources, such as the Warren Communications Cable Fact book (<http://www.warren-news.com/factbook.htm>).

The second and most authoritative form of validation was data received from cable providers at the census tract, block, or coverage level of geography. A spatial join geoprocessing operation was performed on these datasets with the full set of potential cable coverage areas in order to further validate areas with cable coverage.

The third source of validation came from the public speed test site maintained throughout the project. Whenever user submitted speed tests identified cable modem broadband service near or adjacent to existing estimated cable areas, the cable-plus boundaries were expanded using the same method of digitizing outlined above.

It was not possible to differentiate between technology of transmission codes 40 and 41 using this indirect mapping method. The only authoritative way to determine this information was from data submitted by a provider. In all cases where the provider did not indicate the type of cable modem technology being used, the code for Cable Modem-Other (41) was assumed.

DSL Geoprocessing Model

An ESRI geoprocessing model was created to generate coverage areas for DSL providers who did not submit census block or coverage data (i.e., census tract providers). This model is based on typical DSL technology which can provide service up to 18,000 feet from a central office or remote terminal, unless otherwise specified by a provider.

Since DSL lines are typically buried alongside roadways, underneath roadbeds, or strung on aerial telephone lines which tend to run alongside a road, a GIS dataset of a state's road network were used as a surrogate to model DSL areas. In the initial rounds of broadband maintenance we purchased commercial (GeoTel) and publicly available data sources representing last points of aggregation (LPA) for DSL, including central offices and remote terminals. Each LPA was validated based on publicly available data, provider data, and independent measurements. LPAs were used in a DSL model only if they were supplied directly from a provider or could be verified by two or more sources. The actual geoprocessing model used the validated central office and remote terminal locations to generate a raster cost surface based on all of the available roads radiating out 18,000 feet from each active LPA point. The raster coverage was converted to a polygon feature class and a small back-buffer was applied to achieve the final DSL coverage polygon representing a provider's maximum possible DSL coverage area. The DSL coverage areas were then used to select intersecting census blocks and road segments.

Remote terminals were provided or publicly available for only a small number of providers, therefore this method may tend to underestimate the full DSL coverage for a provider.

It was not possible to differentiate between ADSL or SDSL based on the LPA data; the only authoritative way to determine this was from data submitted by a provider. In all cases where the provider did not indicate which type of DSL service was being provided, the technology code was assigned to 10 "Asymmetric xDSL".


2000 TO 2010 Census Block Conversion

The September 2011 deliverable to NTIA required the transition from 2000 census data to 2010 census data, but the conversion process was dependent upon the type of data submitted by a provider. These providers fell into two categories, block providers or coverage providers. The conversion to 2010 census geography was a straightforward process for the coverage providers; the reference to the census block data in the geoprocessing model used to select census blocks and road segments was simply changed from the 2000 data to the 2010 data and each provider's data was re-run. The conversion from 2000 census to 2010 census data for block providers required several geoprocessing steps due to the inability to simply match census block IDs across vintages. The census blocks for each provider were dissolved by type of technology to form a quasi-coverage area. The dissolved blocks were then used to select any 2010 census block whose centroid fell within the "coverage area."

Road Segment Geoprocessing Change

Prior to the September 2011 NTIA data submission, road segments in census blocks greater than 2 square miles were selected with a straight intersect. This resulted in road segments being selected that were coincident with census block edges in blocks less than or equal to 2 square miles. Using this same geoprocessing methodology combined with the new 2010 census blocks and TIGER roads, road segments were selected that were coincident with census block edges and that extended into census block less than or equal to 2 square miles. We believe this "error" occurred due to the improvements in the spatial accuracy of both the 2010 census blocks and road segments for 2010 where features were now coincident. For the September 2011 submittal a small negative buffer (-0.5 feet) was applied to the intersect to avoid selecting roads that were coincident with census block edges and/or those that extended into census blocks less than 2 square miles. This resulted in a significant decrease in the number of road segments reported but overall we believe this method more accurately portrays each provider's coverage area.

Figure 10 Road Segment Geoprocessing Change Example



Wireless Coverage

Three forms of wireless coverage were provided in this table, fixed point to point wireless, mobile wireless and satellite. No public data was located on fixed wireless infrastructure points, except notification of availability on provider's web pages, and in some instances, specific towns, recreation or commercial locations where wireless service was provided. No modeling was attempted on fixed wireless coverage. All coverage came directly from providers or was mapped from locations provided on a provider web page. We did not attempt any propagation modeling on fixed wireless, since that can be influenced by local structures and vegetation in the vicinity. A few providers did provide coverage that appeared to be derived from propagation modeling.

Most of the public data research focused on mobile wireless providers using cellular service spectrums. The Federal Communications Commission (FCC) Universal Licensing System (ULS) is the consolidated database and application filing system for most Wireless Radio Services. ULS supports electronic filing and provides public access to licensing information, weekly Public Notices, FCC rulemakings, processing utilities, a telecommunications glossary, and much more." The FCC ULS Advanced Licensing Search was queried for all FCC licenses filed in the state; a relational database was built from the results. Information from the database was extracted in order to perform the cellular tower propagation modeling for wireless broadband.

The FCC ALS and ULS reporting systems were the source for most of the tower locations. Towers were required to be licensed when they meet specific published criteria. These included some variables that could be modeled with GIS statewide, such as varying proximity to airports and heliports, combined with specific local level criteria not easily obtained or modeled statewide such as the grade construction within proximity of these, and any structure over 200 ft in height. A number of cell towers providing broadband were likely not located in the FCC database. None of the mobile wireless providers were willing to provide infrastructure such as tower locations and parameters, and the coverage provided were very generalized.

Any fixed or mobile wireless antenna or tower location submitted by a provider, or obtained from the FCC that was used in the final processing for wireless broadband coverage was maintained in the operational database for last point of aggregation, and subsequently transferred to Table 3 backhaul and middle mile points.

Providers submitted coverage data in a wide variety of formats, levels of completeness, and at varying geographic scales. All types of data was accommodated and processed whenever possible. An open structure process for submittals was allowed, accepting any data, and

attempting to work with the provider when questions arose. If data was submitted by a provider in a format that did not allow a direct coverage to be mapped, such as a coarse level of geography such as a census tract, or county, feedback was provided to the providers in the form of standardized spreadsheets in an attempt to standardize the inputs, and increase the geographic granularity of the provider data submission. Although each provider had individual characteristics and nuances in their data submissions, some data patterns can be described generalizing the typical types of submissions. In general, for fixed wireless to be mapped it was necessary to receive data from a provider, since there were no public sources available on point to point wireless tower locations in public form, except as depicted on providers web pages in a few instances.

Providers Submitting FCC Form 477 Report or Similar Format

Geographically, these were lists of census tracts of coverage, accompanied by additional documentation on technology of transmission, speed tiers, and number of customers. Providers submit these twice a year to the FCC and recent submissions have been done using a structured web site maintained by the FCC. A few providers submitted printouts that appeared to be from this web format and were typically complete and standardized. More providers submitted spreadsheets roughly in the F477 format, but with modified and generalized data.

How They Were Processed

If the providers identified specific coverage areas as census blocks, or direct coverage area, or as infrastructure tower locations, they were processed and mapped. Providers identifying census blocks were processed by dissolving the census blocks into single coverage polygons by speed tier. Providers identifying a direct coverage area were converted directly to GIS polygon files and attributed. Providers submitting tower locations were mapped as circular polygons centered on the tower with a radius averaging 10 miles measured as Euclidian (straight line) distance from the tower. Providers that specified variable radius were mapped as circles at the radius they submitted.

Providers Submitting Census Block Coverage

A few providers submitted coverage as census blocks, either through a tabular listing of census blocks or spreadsheet, or in map format. It was common that a provider where public data indicated multiple technologies of transmission only submitted some of the technologies of transmission.

How They Were Processed

These were loaded directly into the master Census 2000 block coverage by provider and attributed with available data submitted by the provider. In instances where some data attributes were missing, such as advertised or typical speed tiers, or subscriber data, the data attributes were left blank or null. Providers identifying census blocks were processed by

dissolving the census blocks into single coverage polygons by speed tier. A visual inspection of independent speed test data overlaying the provider submitted block coverage was completed, but no action was taken to override a provider's submittal.

Providers Submitting Actual Coverage Maps

Coverage maps were submitted by several providers, or coverages were derived from public sources or from other indirect indicators of coverage such as customer point maps or tabular lists in text or spreadsheet format. These were differentiated from the other types of geographic submission coarser than a census block since they represented the full and explicit range of coverage.

How They Were Processed

Coverage maps were treated as explicit coverage and all census blocks intersecting any portion of a coverage were selected and attributed with the provider coverage by technology of transmission, and all related attributes were transferred to the census block representation. The method of creating the coverage varied by source. Providers who supplied broadband coverage as a GIS polygon or CAD feature were converted to polygons. Some providers, including non-responsive providers who did not submit anything to the project, had published coverage maps of various forms on their web sites or submitted an image in jpg, tiff, pdf or other graphic format. These were georectified to base map layers, typically roads, but sometimes other features such as state or county boundaries or towns, and subsequently converted to polygon features. Then they were intersected and transferred to census block feature classes like the digital GIS submissions. Providers who submitted customer locations typically fell into four categories. Some were submitted as AutoCAD files where the points could be transferred to the GIS, then spatially joined to the census blocks they were located within. Others submitted maps in image format that were georectified in the same manner as other images, then census blocks were selected by an operator viewing the customer point images underlying the census blocks. When customer lists were submitted, they were loaded in a database and geocoded using ESRI Business Analyst USA Geocoding engine based on TeleAtlas road features. The geocoded points were subsequently treated identically to customer locations submitted in GIS or CAD format, and spatially joined to the census block template file. A visual inspection of independent speed test data overlaying the provider submitted block coverage was completed, but no action was taken to override a provider's submittal.

Providers Submitting Other Levels of Coarse Geographic Submission

This category had a wide range of submissions. The most common was as telephone exchange areas or equivalent, wire centers, zip codes, counties or general references to towns or cities. The problem with these submissions was that often a given polygon overlapped a census block or multiple blocks, and in most cases, they were much larger geographic entities than a census block.

How They Were Processed

Our operating rules established early in the project did not allow final provider coverage to significantly over represent provider coverage. Those providers that submitted coverage area by coarse geographic features and did not specifically identify coverage as a coverage layer or census blocks were not able to be processed. No interpolated data was used to calculate these data, if the data was not provided by a provider in a format capable of processing; the data was not calculated for that provider.

Satellite

Satellite coverage for the entire state was included for the three satellite providers: HNS License Sub, LLC, StarBand Communications Inc., and WildBlue Communications, Inc.

Community Anchor Institutions

Lists were obtained from the state and affiliated professional organizations for anchor institutions to be included in the broadband mapping in each of the community anchor institution community code categories. These were sorted and cross referenced and an initial round of elimination of duplication was accomplished.

All institutions on the initial draft spreadsheets used for the first two submittals were geocoded using ESRI Business Analyst Desktop with the USA Geocoding engine using TeleAtlas premium road features. This was judged to be the best available geocoding source for batch processing of addresses. No commercial source is 100% accurate in a primarily rural state such as this with low population numbers compared to other states and no large cities or metropolitan statistical areas. In subsequent rounds of updates since the first two submittals, we have used the same geocoding engine from Esri Business Analyst, but the geocoding locator switched to NavTech geocode locator. In every round of geocoding we used conservative matching criteria, and maintained and stored the type of match (building match, address match, or zip code match), along with a record of those not matching and not able to geocode.

All geocoding is dependent on accurate road locations and complete and accurate street segment attribution. The GIS road layers available from the state were not judged as complete as the premium commercial sources. The Tiger 2009 road files, while spatially comparable to the commercial sources, have a large percentage of null values in the database attribution and street segment address ranges necessary for accurate geocoding. As in most parts of the country, geocoding is more accurate in urban settings than in rural routes. Complicating the process in a rural state for anchor institutions are the situation where some anchor institutions, such as public safety anchors are often staffed by volunteer staff and a post office box is the

only valid address, and the physical address is wherever the public safety equipment is parked or stored at any given point in time.

Category codes were assigned based on the original source list and from keywords in the name of the institution and independent research. Technology of transmission and advertised speeds were obtained when possible, which initially was entirely based on the anchor institutions maintained by the state for consortiums providing state service contracts. Two iterations were accomplished with these state maintained lists, and all available attributes were obtained with assistance of the state analysts.

After initial data collection, analysts worked on researching, calling and improving the addresses for those below an 80% match criteria. Many on the 70 percent matching range were fairly accurately located. The difference between a 70% and 80% match typically occurred when an address lacked a prefix or suffix cardinal direction on a street that had two cardinal directions (example 101 1st Street, on a street segment with 101 N. 1st Street and 101 S. 1st Street). Analysts were also able to obtain physical addresses for some lists supplied by the state with only a P.O. Box.

The lists with updated and corrected addresses were re-geocoded for the final mapping effort, and any anchor with any level of geocoding was included on the final map. The operational database identifies the type of match, so future maintenance cycles can be prioritized and targeted to those matching only zip codes or with address changes.

From the results of the previous step some attribution of database attributes for attributes with null values was accomplished. This step was rule based. The attribute of whether an anchor institution subscribes to broadband service could only authoritatively be answered yes, if the information was provided by the state, or a confirmation from an anchor speed test could be matched. Those anchors that were located within an area covered by a DSL, cable, other copper or fixed wireless were also assumed to have the ability to subscribe to broadband coverage and were also estimated to be subscribers. Assigning the technology of transmission and the advertised speeds (which required identifying a provider for the anchor institution) was only possible on a subset of all coverage in those areas where only one provider/technology of transmission was present. This allowed a few hundred more anchors to be identified, but typically only occurred in rural settings. Most urban settings had multiple providers. In addition many providers submitted multiple technology options, so identifying one provider/technology of transmission combination was not possible even if there was only one provider possible for the anchor institution.

It is likely that in some instances in the rural settings and small towns an anchor institution may rely on mobile wireless broadband. This is common in public safety mobile equipment such as vehicles, but likely less common in anchor facilities. For the purpose of assigning attribution to

anchor institutions with remaining null attributes, we took a conservative approach and did not overlay anchor institutions on mobile wireless coverages to assign attributes.

Maximum advertised downstream and upstream speeds were not available or collected for any of the CAIs. A new domain value of “U” for Unknown was added to the data model for the current submission, and all values formerly coded as 0, were changed to “U”.

A new optional attribute was requested by NTIA requesting knowledge about the presence or absence of WIFI at the CAI location. This was not researched and attributed by the state in the current submission. All records were set to “Unknown” for the attribute, Public Wi-Fi.

In the first two submission processes for geocoding we used conservative matching criteria, and maintained and stored the type of match (building match, address match, or zip code match), along with a record of those not matching and not able to geocode.

A new optional attribute was requested by NTIA after the initial maintenance updates requesting a CAI unique identification number for K-12 schools, libraries and colleges and universities. The following steps were completed for this request: Added CAIID for the Library category using the NCESID from <http://nces.ed.gov/surveys/libraries/librarysearch/>; Added CAIID for the University, college, other post-secondary category using the IPEDS ID from <http://nces.ed.gov/collegenavigator/>; Added CAIID for the School – K through 12 category for public schools using the NCES ID from <http://nces.ed.gov/ccd/schoolsearch/>; Added CAIID for the School – K through 12 category for private schools using the PSS_SCHOOL_ID from <http://nces.ed.gov/surveys/pss/privateschoolsearch/>

A new optional attribute for the URL for each anchor institution was requested by NTIA. Assigned URLs to CAI records: for the University, college, other post-secondary category assigned the URL from <http://nces.ed.gov/collegenavigator/>; for the Library category added the URL from <http://nces.ed.gov/surveys/libraries/librarysearch/>

Middle Mile

Middle mile and backhaul points were included for all public data and provider submitted infrastructure judged to be reliable and valid. A systematic reliability (geographic scale and authority of the source) rating and a validity rating (cross referencing between multiple sources) were developed and used throughout the project, both on a scale of 1-10, along with feature level metadata to maintain the last point of aggregation. A persistent unique identifier was used to track each point and each instance of a point as they moved through the system and improved in quality. Old points were retired but were not deleted from the operational database. Only active records were used in the final processing.

A feature class labeled "Last point of aggregation" (LPA) in the operational database was created to hold point locations of broadband infrastructure (examples include central offices, remote terminals, head ends, etc.). Addresses purchased or obtained at any level of geography were geocoded to a street address (using ESRI Business Analyst and TeleAtlas data) or located more generally to the center of a town (snapped to the USGS Geographic Names Information System location) when no address information was available. and All mobile wireless locations obtained from public sources or commercial sources that were not already validated were confirmed using NAIP aerial imagery and Google Street View (when available). All FCC tower locations included a latitude and longitude, however all towers were validated and moved to the NAIP aerial imagery location.

A reliability code indicating the source and geographic scale represented as an integer from 1 (low) to 10 (high) was assigned. Validity codes were assigned cross-referencing public and provider data submissions; it was also rated on a scale of 1-10. A point with a validity code of 7 that fell within a provider's coverage for DSL, mobile or fixed wireless, or was used in a final modeled coverage was included in this table. In addition, backhaul points identified by the state, by providers and consortiums providing services to the state and anchor institutions, were included in the table. Providers were typically reluctant or unwilling to provide infrastructure data, and often unwilling to confirm data obtained through public sources. The methods used in the state allowed a significant level of identification and mapping of infrastructure locations and feature level metadata on reliability and validity of point locations, but data on owned or leased characteristics, serving facility codes, and for elevation of infrastructure was confirmed by few providers who responded directly in a spreadsheet provided to them to list infrastructure.

Speed Test Data Processing

A public facing website was created in the spring of 2010 asking internet users in the state to complete a brief survey regarding their internet connection and run a speed test on their connection using the Ookla speed test. The speed test site asked that a user enter their location as an address on a Google map interface. If the address did not geocode to their satisfaction, the user could choose to move the place mark to their desired location. Next, users were asked to select their technology of transmission from a list, enter their provider in a free form text field, complete an optional questionnaire, and run a standard speed test on their connection. The date and time, and IP address of the user were captured during the speed test.

All speed tests were geocoded, and the IP address was looked up in batch mode in the WHOIS database returning one or two providers registered with WHOIS. All speed tests were cleaned and analyzed against provider submissions and models. For the first two submissions a final

provider assignment was assigned by examining the WHOIS fields, and the provider submitted by users. Consistent rules were not always possible, but generally when two WHOIS records were returned, the second more specific WHOIS provider was selected. In some instances, where the WHOIS providers were backhaul or other and were not providers meeting the NOFA criteria, the user submitted provider designation was cleaned and standardized and assigned as the final provider

There was considerable variation between the user reported technology of transmission (TOT) and the known technologies for any given provider. Records were divided on unique provider/TOT combinations for the first and second submissions, which limited the record count in many instances. For the current submission the records were divided only by provider, not taking TOT into consideration.

For the first two submissions, the speed test records were used in two ways for the final processing.

1) As an independent measurement to validate the presence/absence of a provider coverage for DSL and/or Cable technologies.

In the first submission a few providers were identified as DSL broadband providers based primarily on speed tests. In these instances, DSL models were executed for both providers based on verified central office locations. Some speed tests with an identified technology of transmission of Cable Modem were used to expand “likely” cable areas which were typically adjacent to incorporated and urban areas. These “cable-plus” areas were created to supplement submissions from Cable Modem providers who did not provide detailed coverage or census blocks. No new DSL providers or Cable providers were identified using speed tests in the current submission.

2) As an independent measurement for typical upload and download speeds.

Once data were cleaned and final provider and technology of transmission assigned, these fields were concatenated. In the first two submissions, if the remaining records exceeded 10 for the combination of provider and technology, and the speed test was successfully completed (values > 0) the average value and standard deviation of the download speed were calculated. Any values exceeding 1 standard deviation were removed as outliers, and the mean of the remaining records within 1 standard deviation was calculated for the download and upload speed. This value was reported for each provider/technology of transmission record as the typical speeds for that provider. In some instances the typical speed was lower than that required to meet the definition of broadband by NTIA, but that did not preclude the records from being included in the broadband map in the first two submissions as it did in the current submission.

For the current submission, these procedures were modified and all records were re-run. The steps of the current processing are provided below. The primary procedural change was to drop the validation of the presence/absence of provider coverage for DSL and/or Cable technologies, since providers had been validated in the first two submissions and potential new providers identified through additional speed tests were determined to not meet the NOFA criteria for being considered a broadband provider. The use of the speed test data for determining typical speeds was implemented with similar rules as the first two submissions with the exception of the use of the technology of transfer, and raising the minimum number of speed tests to 15, after removing outliers, to be used in typical speed calculations. Procedurally, the process was also automated with a Python script to improve processing performance and minimize quality control/quality assurance testing.

Typical upload and download speeds for all providers with less than 15 processed speed test records were coded as null values. In addition, based on telephone communication with NTIA on March 9, 2011, all typical speeds less than minimum NOFA upload of download speed criteria were also ignored and reported as null. Based on a related request in the same communication, the typical speeds greater than the advertised speeds were ignored and reported as null. Processing steps for the current submission are provided below:

1. Speed test records were imported into a SQL Server data file, adding fields Final Provider and IPGroup to the initial records.
2. IPGroup attribute was set by extracting the left three nodes of the IP Address of the speed test (e.g. 161.7.1.236 had 161.7.1) moved to the IPGroup attribute.
3. An IPGroup to Final Provider cross reference table was created to determine the final provider from the unique three part IPGroup.
4. Each IPGroup was reviewed with the data in the WHOIS 1 provider, WHOIS 2 provider and then the user specified provider to determine the most authoritative final provider from the official list of providers. None of the WHOIS or user submitted fields were absolutely authoritative in all instances, so expert opinion by technicians knowledgeable of the providers was used in some instances to assign the IPGroups, and subsequently the Final Provider attribute.
5. Run a python script to remove outliers and calculate summary statistics for each Final Provider assignment. The rationale for removing outliers was to mitigate the many variables that effect a typical speed test, such as the time of day, others on the network, etc. The script implemented the following work flow rules:

- a. Use all records for each unique FinalProv attribute value with D_kbps greater than 0 or U_kbps greater than 0 , then:
 - b. Calculate a mean for the unique provider group for each D_kbps and U_kbps.
 - c. Calculate a standard deviation for the unique provider group for each D_kbps and U_kbps. Each speed attribute was calculated independently of the other.
 - d. Subtract the outliers (if any) higher or lower than one standard deviation from the mean.
 - e. Calculate the median value of the remaining non-outliers for each provider D_kbps and U_kbps respectively.
 - f. Create a summary table with the final calculated assignment of FinalProv, D_kbps and U_kbps.
6. Post process the summary table in the following sub steps:
- a. Join the summary tables by provider for the upload and download speeds into one summary file including the number of records or frequencies for up and down speeds for each provider after removing the outliers, and the mean up and down speeds in kilobits per second for each provider.
 - b. Select "FreqDown" < 15 AND "FreqUp" < 15 then delete the resulting selection set from the joined table. The FreqDown/Up fields counted the number of speed test records for a provider after the outliers more or less than one standard deviation from the mean value were removed from consideration.
 - c. Select "D2_kbps" <= 768 kbps AND "U2_kbps" <= 200 kbps. then delete the resulting selection set from the joined table.
7. Import the remaining valid mean values for each provider into the appropriate broadband coverage feature classes.
8. Select any typical speeds greater than advertised speeds either up or down, and make the resulting records null in the final broadband coverage feature classes (as per NTIA request 3/9/2011).

Reliability, Validity and Completeness

Reliability codes apply to the source data points and polygons and assess the authority of the source we obtained the data from and the level or coarseness of the geography (address or town). Validity codes are determined from cross checks of data sources and the number of independent sources of verification. These are as simple as comparing speed test locations against DSL modeled polygons, or as complex as geospatial analysis operations such as a kernel density function cluster analysis. Completeness is determined by public sources, independent measurements or provider submittals and checks on the domain classes required for the final NTIA deliverables such as Technology of Transmission domains, Speed Test domains and serving facility and wireless spectrum facility types and categories. The categories for these, and the subsequent records in our operational geodatabase tables have the ability to grow and change as new data is obtained. New data for wired We are maintaining these as feature level metadata tied to points and polygons maintained by analysts and technicians in a wiki table and coding them to the geodatabase. In this way the unique situations that arise can be cataloged and maintained with some level of flexibility while contributing to the final indices in a controlled fashion.

Reliability Codes

Throughout the course of the broadband project the State of North Dakota has employed several validation and verification techniques to help quantify the accuracy of the broadband map. The techniques used are listed below:

- Reliability Codes Assigned to Infrastructure Points
- State Run Speed Test Portal
- State Wide Broadband Survey

The two factors incorporated in reliability codes include the level of geography that was used as a source or provided as a clarification of location and the authority of the source for the information. We are also considering clusters of point information from independent measurements and sources to be higher in reliability than individual point information.

Generally, the coarser the source geography the lower the resultant score. Everything besides an address or street intersection, latitude/longitude location, or location provided in a georeferenced digital source is assigned a reliability score less than 5. This applies to source data coming (e.g. a central office located in a city instead of an address) and review comments on a previously mapped location (e.g. "That location is wrong, I know it is on the south side of town").

We have incorporated the reliability code into our last point of aggregation (LPA) and provider coverage geodatabase files, and into some of the publicly available data (PAD) geodatabases.

We are also carrying a short text field (50 characters) with a descriptive rationale for the score. This will allow us to focus more on the lower scores that need to be confirmed, and ignore the high confidence data scored as 9 and 10.

Reliability Codes		
Code	Description	Detailed Description
0	Not assigned	<ul style="list-style-type: none"> Not yet assigned
1	Level 1	<ul style="list-style-type: none"> Checked but unverified
2	Level 2	<ul style="list-style-type: none"> County Presence by other coarse geography (e.g. administrative region)
3	Level 3	<ul style="list-style-type: none"> City Census tracts Cable Plus (area likely to have been annexed into an incorporated town or CDP)
4	Level 4	<ul style="list-style-type: none"> Cable - incorporated Zipcodes Census blocks
5	Level 5	<ul style="list-style-type: none"> GeoTel unverified Confirmed by provider or anchor institution key advisor but to geography coarser than address or intersection
6	Level 6	<ul style="list-style-type: none"> Qwest/Midcontinent or other web site random testing check Speed test from individual average residential
7	Level 7	<ul style="list-style-type: none"> From anchor institution key advisor Webex GeoTel verified address only with no 3rd party confirmation from public sources <ul style="list-style-type: none"> Building unverified Speed test from anchor institution
8	Level 8	<ul style="list-style-type: none"> From provider FCC ULS or ARS Geotel verified address and possibly verified by 3rd party source (Google Streetview) <ul style="list-style-type: none"> Another provider's sign is on building (usually Qwest) Geotel possibly verified by 3rd party source (NAIP, Google Streetview) From state authoritative public data source (e.g. DCN or SummitNet) <ul style="list-style-type: none"> Address or building unverified Speed test from cluster of average residential
9	Level 9	<ul style="list-style-type: none"> From provider as coverage with authoritative confirmation Geotel verified address and verified by 3rd party source (NAIP, Google Streetview) <ul style="list-style-type: none"> Provider sign on building Tower or dish visible From provider or anchor institution check of our data * Root Wireless
10	Level 10	<ul style="list-style-type: none"> From 2+ authoritative confirmations

Validity Codes

We included validity codes in the last point of aggregation infrastructure data which drives creation of the DSL models. We also included validity codes in each of the final technology of transmission deliverables for polygons and point feature classes. The scales of validity vary by each major type and function.

Infrastructure Validity Codes

The purpose of this validity code is twofold:

1. To determine which infrastructure points are turned into DSL model coverages
2. To use as a reference in other coverage validity checks

Infrastructure Validity Codes		
Code	Description	Detailed Description
0	Level 0	<ul style="list-style-type: none"> • Not yet assigned
1	Level 1	<ul style="list-style-type: none"> • Not yet assigned
2	Level 2	<ul style="list-style-type: none"> • Not yet assigned
3	Level 3	<ul style="list-style-type: none"> • Checked against ND PSC Report or DSLReports at the town level • Checked against DCN anchor institution data
4	Level 4	<ul style="list-style-type: none"> • Checked against two or more independent public sources at the town level • Checked against provider public data (e.g. Qwest ICONN) at the town level
5	Level 5	<ul style="list-style-type: none"> • Not yet assigned
6	Level 6	<ul style="list-style-type: none"> • Confirmation of DSL or cable from authoritative public data to broader geography than address not confirmed by provider
7	Level 7	<ul style="list-style-type: none"> • Authoritative public data at address level (e.g. Geotel) not confirmed by provider
8	Level 8	<ul style="list-style-type: none"> • Provider submission at the census tract level • Provider website independent address checks (Qwest, Verizon)
9	Level 9	<ul style="list-style-type: none"> • Provider submission at the census block level or address level
10	Level 10	<ul style="list-style-type: none"> • Provider submission at the coverage level at census block scale or blocks less than 2 square mile and larger scale then census block for blocks larger than 2 square miles

Final Technology of Transmission Validity Codes

The purpose of this validity code is twofold:

1. To determine which elements are loaded in the spreadsheet provider submission packages in their review

2. To determine which provider coverages are chosen for submittal with one of the NTIA deliverables

Final Technology of Transmission Validity Codes		
Code	Description	Detailed Description
0	Not assigned	<ul style="list-style-type: none">• Not yet assigned
1	Level 1	<ul style="list-style-type: none">• Unassigned at this time
2	Level 2	<ul style="list-style-type: none">• Unassigned at this time
3	Level 3	<ul style="list-style-type: none">• Checked against ND PSC Report or DSLReports at the town level• Checked against DCN anchor institution data
4	Level 4	<ul style="list-style-type: none">• Checked against two or more independent public sources at the town level• Checked against provider public data (e.g. Qwest ICONN) at the town level
5	Level 5	<ul style="list-style-type: none">• Confirmation of DSL or cable from authoritative public data
6	Level 6	<ul style="list-style-type: none">• Provider website independent address checks (Qwest, Verizon)• Provider submission at the census tract level
7	Level 7	<ul style="list-style-type: none">• Provider submission at the census block level• Provider submission at the census block level confirmed by Speed test cluster OR other independent measurement
8	Level 8	<ul style="list-style-type: none">• Provider submission at the address level
9	Level 9	<ul style="list-style-type: none">• Provider submission at the address level confirmed by Speed test cluster OR other independent measurement
10	Level 10	<ul style="list-style-type: none">• Provider submission at the address level confirmed by Speed test cluster OR other independent measurement

Quality Assurance Testing

A separate analyst checked each provider submission. Due to the variety of provider submissions, the analyst originally doing the work and the analyst checking discussed the interpretations when the criteria were subject to interpretation.

Coverage, technology of transmission, and speed tier were checked completely for each provider.

Many of the models and block, tract and coverage level processes were completed with ESRI Modelbuilder and Python scripts, and these methods were tested for quality assurance in the preliminary mapping stages and in the initial sample data submissions to NTIA.

All providers who submitted geographic coverage coarser than a census block were provided a data checking package to assess for accuracy and completeness. Any comments received from providers were processed.

1. QA/QC Checks prior to Individual Data Processing (i.e., block or coverage geoprocessing model). [Automated Modelbuilder tools and follow-up by an analyst]
 - a. Check for inconsistencies within the Provider Name, DBA Name, FRN
 - b. Check for duplicate census blocks or coverage areas
 - c. Check the Provider Name, DBA Name, FRN against the “Official Provider Table”
2. For each provider after initial data processing is completed [Review by an analyst that did not process the original data]
 - a. Review correspondence log
 - i. Review recent correspondence, since previous NTIA submission
 - ii. Note changes/additions/comments on coverage area, technologies, speeds, infrastructure, subscriber weighted nominal speeds (SWNS)
 - b. Review wiki data processing page (current metadata)
 - i. Note changes/additions/comments on coverage area, technologies, speeds, infrastructure, SWNS
 - c. Review individual Provider Wiki page (historic metadata)
 - i. Note changes/additions/comments on coverage area, technologies, speeds, infrastructure, SWNS
 - d. Check Provider Data Folder
 - i. Review recent data submissions, since previous NTIA submission
 - e. Check Working Data Folder
 - i. Review current update feature class geography
 - ii. Review coverage with provider’s submissions
 - iii. Review technology of transmissions (TOTs) with provider’s submissions
 - iv. Review Max Adv Speeds: Down/Up with provider’s submissions
3. For each provider after final data processing is completed [Review by an analyst that did not process the original data]
 - a. Check PROVCOV_Master geodatabase:Provider Blocks feature class and/or Provider Coverage feature class
 - i. Review geography
 - ii. Review TOTS
 - iii. Review Max Adv Speeds: Down/Up
4. Check Infrastructure feature class [Review by an analyst that did not process the original data]
 - a. Review recent submissions, since previous NTIA submission
5. Check SWNS feature class [Review by an analyst that did not process the original data]

- a. Determine if provider submission is valid
6. For each provider after speed tests are processed [Review by an analyst that did not process the original data]
 - a. Check PROVCOV_Master geodatabase for Typical Speeds: Down/Up
7. QA/QC Checks and Reports on the Final NTIA Deliverable [Automated Modelbuilder tools and follow-up by an analyst]
 - a. Check the Provider Name, DBA Name, FRN against the “Official Provider Table” for each NTIA feature class (i.e., BB_Service_CensusBlock, BB_Service_RoadSegment, BB_Service_Wireless, etc.). NTIA_Provider_Name_DBA_FRN_Errors_Sample.xls, looks at each NTIA feature class (i.e., census blocks, road segments, wireless, etc...) and checks to see if there is an identical match in the “Official Provider Table.” If an identical match does not exist for that Provider Name, DBA Name, FRN concatenation it is written to a geodatabase table along with the NTIA feature class where the “error” occurred. When an “error” does occur it then has to be checked by an analyst and corrected if necessary.
 - b. Change Detection Report – This geoprocessing model compares and reports any changes in the Census Block, Road Segment, and Wireless feature classes for the current and previous versions of the NTIA SBDD Transfer database. The user needs to supply the feature classes for each NTIA version as well as the name of the final change detection table. NTIA_Change_Detection_Example.xls, compares and reports any changes (limited to Provider Name, DBA Name, FRN, TOT combinations) in the Census Block, Road Segment, and Wireless feature classes for the current and previous versions of the NTIA SBDD Transfer database. If the final change detection table has no records, then no changes were detected between the two databases. If a Provider Name, DBA Name, FRN, TOT combination does not have a “pair” in either direction (the current or previous NTIA database) then it is written to a geodatabase table along with the NTIA feature class and version where the “error” occurred. This report does not change any data in either database but rather acts as a flag, requiring an analyst to check if the “error” is valid.
 - c. Check for duplicate census blocks or road segments or wireless coverage areas.
 - d. Check for duplicate anchor institution points.
8. Review Final NTIA deliverables [Review by an analyst that did not process the original data]
 - a. Review BB_ConnectionPoint_MiddleMile
 - b. Review BB_Service_CAInstitutions
 - c. Review BB_Service_Census Block
 - d. Review BB_Service_Overview

- e. Review BB_Service_RoadSegment
 - f. Review BB_Service_Wireless
9. Run the NTIA Check submission tool and python tool to confirm that all possible records passed the NTIA data checks. The only items that failed in the checking process were those where inconsistencies in the final NTIA NSGIC data model did not agree with the final documentation and rules established by NTIA and FCC in the final webinar and documentation presented March 17, 2011. These exceptions were documented along with the submission.

Appendix A

Potential providers researched but subsequently identified as not providing broadband service.

Company Name	Filing Company DBA	FRN	URL
5LINX Enterprises Inc. dba Globalinx	5LINX Enterprises, Inc.	0015304645	5linx.com/products
8x8, Inc.	8x8, Inc.	0007099773	www.8x8.com
Ablaze Technologies			none
ACN Communication Services, Inc.	ACN Communication Services, Inc.		www.myacn.com/index.html
Alltel Wireless	Alltel Wireless		na
American Fiber Network, Inc.	MobilePro Corp.	0006801583	none
AT&T Corp.	AT&T Inc.	0004496774	www.att.com
AxisInternet, Inc.	AxisInternet, Inc.	0019609254	www.axint.net
Badlands Cellular of North Dakota Cellular Partnership	Verizon Communications Inc.	0018535716	none
Bandwidth.com, Inc.	Bandwidth.com, Inc.	0015443773	bandwidth.com
BroadvoxGo!, LLC	BroadvoxGo!, LLC	0017679523	www.broadvox.com
Broadwing Communications, LLC	Level 3 Communications, LLC	0008599706	www.level3.com
BullsEye Telecom, Inc.	BullsEye Telecom, Inc.	0004350930	www.bullseyetelecom.com
Call Catchers Inc.	Call Catchers Inc.	0016109803	none
Callsmart	Callsmart		http://www.getcallsmart.com/
Cause Based Commerce Incorporated	Cause Based Commerce Incorporated	0015173503	causebasedcommerce.com
CierraCom Systems	CierraCom Systems		www.cierracom.com
Citizens Communications	Citizens Communications		none
CommPartners, LLC	CommPartners, LLC		www.commpartnersconnect.com
Consolidated Communications Networks, Inc.	Consolidated Telcom	0003740396	www.ctctel.com
Covad Communications Company	Covad Communications Company		www.covad.com/
CrossConnect	CrossConnect		www.crossconnectsolutions.com/
CVC CLEC, LLC	CVC CLEC, LLC		www.cvcclerc.com
Cypress Communications, Inc.	Cypress Communications, Inc.	0005038930	cypresscom.net
Daktel Communications, LLC	Dakota Central Telecommunications	0007266703	www.daktel.com

	Cooperative		
DIECA Communications, Inc.	DIECA Communications, Inc.		www.covad.com
Digital Telecommunications, Inc.	Digital Telecommunications, Inc.		digitaltel.com
DSLnet Communications, LLC	DSLnet Communications, LLC		www.megapath.com
Enventis Telecom Inc.	Hickory Tech Corporation	0008394322	www.enventis.com
Ernest Communications, Inc.	Ernest Communications, Inc.	0004948642	www.ernestgroup.com
Ethos Communications Group, Inc.	Ethos Communications Group, Inc.		www.ethoscommunications.net
Exit Mobile	Exit Mobile		www.exitmobile.com
Faith Communications, Inc.	Faith Communications, Inc.		www.faith-inc.com
First Communications, LLC	First Communications, LLC	0003764487	www.firstcommunications.org
France Telecom Corporate Solutions L.L.C.	France Telecom Corporate Solutions L.L.C.		www.francetelecom.com
Frontier Informatics LLC	Frontier Informatics LLC		www.frontiertelco.com
Frontier Telco	Frontier Telco		www.frontiertelco.com
Global Crossing Telecommunications, Inc.	Global Crossing North America, Inc.	0002850519	www.globalcrossing.com
Grand Forks Wireless	Grand Forks Wireless		www.grandforkswireless.com
Granite Telecommunications LLC	Granite Telecommunications LLC	0008676975	www.granitenet.com
Great Western Network	Great Western Network		www.greatwesternnetwork.com
GreatCall, Inc.	GreatCall, Inc.	0018554386	www.greatcall.com
Greenfly Networks, Inc.	Greenfly Networks, Inc.	0015808736	www.clearfly.net
Harris Corporation	Harris Corporation		www.harris.com
Hypercube Telecom, LLC	Hypercube Telecom, LLC		www.h3net.com
iCore Networks, Inc.	iCore Networks, Inc.	0015340326	www.icore.com
InPhonex.com, LLC	InPhonex.com, LLC	0010488351	www.inphonex.com
Integra Telecom of North Dakota, Inc.	Integra Telecom Holdings, Inc.	0005071014	www.integratelecom.com
Ionex Communications North, Inc.	Birch Communications Inc.	0005027305	www.birch.com/about/
IP Networked Services, Inc.	IP Networked Services, Inc.	0016088882	none
KDDI America, Inc.	KDDI America, Inc.		www.kdd.com

North Dakota Broadband Mapping
October 1, 2012 Methodology Report

Kentucky Data Link, Inc.	Kentucky Data Link, Inc.		www.kdlink.com
Kotana Communications, Inc.	Kotana Communications, Inc.		kotana.com
Level 3 Communications, LLC	Level 3 Communications, LLC	0003723822	www.Level3.com
LightEdge Solutions, Inc.	LightEdge Solutions, Inc.	0015546443	www.lightedge.com
LightSquared LP	LightSquared LP	0007705742	www.lightsquared.com
Lightyear Network Solutions, LLC	Lightyear Network Solutions, LLC		www.lightyear.net
Loretel Systems, Inc.	Hector Communications Corporation	0002650828	www.loretel.com
Matrix Telecom, Inc.	Matrix Telecom, Inc.	0004333068	www.matrixbt.com
MCImetro Access Transmission Services LLC	MCImetro Access Transmission Services LLC		www.verizon.com
McKenzie Consolidated Telcom, LLC	McKenzie Consolidated Telcom, LLC		none
McLeodUSA Telecommunications Services, Inc.	PaeTec Corporation	0003716073	www.mcleodusa.com
Metropolitan Telecommunications of North Dakota, Inc.	Metropolitan Telecommunications Holding Company	0009806019	www.mettel.net
Millicorp	Millicorp	0018930511	www.millicorp.com
Missouri Valley Communications, Inc.	Nemont Telephone Cooperative, Inc.	0008326787	www.nemont.net
Mix Networks, Inc.	Mix Networks, Inc.	0014166573	www.mixnetworks.com
Mobile ESPN, LLC	Mobile ESPN, LLC		www.espn.com
NB Internet LLC	NB Internet LLC		www.nbinternet.com/
Network Innovations, Inc.	Network Innovations, Inc.		www.nitelecom.com
Neutral Tandem-North Dakota, LLC	Neutral Tandem-North Dakota, LLC		www.neutraltandem.com
New Edge Network, Inc.	New Edge Holding Company	0003720471	www.newedgenetworks.com
nexVortex, Inc.	nexVortex, Inc.	0015282155	www.nexvortex.com
Noonan Farmers Tel Co	Noonan Farmers Tel Co		
Norlight Telecommunications, Inc.	Norlight Telecommunications, Inc.		www.norlight.com
Norlight, Inc.	Norlight, Inc.		www.norlight.com
Northern Red River ITV	Northern Red River ITV		www.nrritv.k12.nd.us
Northstar Telecom, Inc.	Midwest Marketing	0011412905	www.northstartelecom.us

	Group, Inc.		
NOSVA Limited Partnership	NOSVA Limited Partnership		nosva.com
OnWav, Inc	OnWav, Inc	0018007898	www.onwav.com/home
PAETEC Communications	PAETEC Communications		www.paetec.com
Phone.com, LLC	Phone.com, LLC	0016845190	www.phone.com
PNG Telecommunications, Inc.	PNG Telecommunications, Inc.		www.powernetglobal.com
PowerNet Global Communications	PowerNet Global Communications		www.powernetglobal.com
Proximiti Technologies, Inc.	Proximiti Technologies, Inc.	0016431603	www.proximiti.com/default.aspx
Qwest Communications Company, LLC	Qwest Communications International, Inc.	0003605953	centurylink.com
Qwest Corporation	Qwest Corporation		centurylink.com
RNK, Inc.	Wave2Wave Communications, Inc.	0004343737	www.wave2wave.com
Rural Cellular Corp. DBA RCC Network Inc	Rural Cellular Corp. DBA RCC Network Inc		www.unicel.com
Sage Telecom, Inc.	Sage Telecom, Inc.		www.sagetelecom.net
Sagebrush Cellular, Inc.	Nemont Telephone Cooperative, Inc.	0001608645	www.nemont.net
SDN Communications	SDN Communications		www.sdncommunications.com
Skycasters LLC	Skycasters LLC	0018756155	www.skycasters.com
Skyland Technologies, Inc.	Skyland Technologies, Inc.		none
Smartnet, Inc.	Smartnet, Inc.		www.getcallsmart.com
South Dakota Network, LLC	South Dakota Network, LLC		www.sdncommunications.com
TDS Telecommunications Corporation	Telephone and Data Systems, Inc.	0004948105	www.teldta.com
TeleCommunication Systems Corporation of Maryland	TeleCommunication Systems Corporation of Maryland		www.telecomsys.com
Telesphere Networks Ltd.	Telesphere Networks Ltd.	0015328032	www.telesphere.com
The Neighborhood, Built by MCI	The Neighborhood, Built by MCI		www.verizon.com
Time-Warner	Time-Warner		www.timewarner.com
T-Mobile	T-Mobile		www.t-mobile.com
Trans National Communications	Trans National Communications	0004337846	www.tncii.com

International, Inc.	International, Inc.		
Trinsic Communications, Inc.	Trinsic Communications, Inc.		www.matrixbt.com
tw telecom holdings inc.	tw telecom inc.	0014942668	www.twtelecom.com
U.S. Link, Inc.	U.S. Link, Inc.		www.tdstelecom.com
UC	UC		www.integratelecom.com
Venture Communications Cooperative, Inc.	Venture Communications Cooperative, Inc.		www.venturecomm.net
Venture Communications Cooperative, Inc.	Venture Communications Cooperative, Inc./Western T	0003784477	www.venturecomm.net
verizon business global llc dba verizon business	Verizon Communications Inc.	0010856284	www.verizon.com
Vision Systems	Vision Systems		www.vision-systems.com
VoIP360, Inc.	VoIP360, Inc.	0016868317	none
VoIPStreet, Inc.	VoIPStreet, Inc.	0016266157	www.voipstreet.com
Vonage Holdings Corp.	Vonage Holdings Corp.	0018401844	www.vonage.com
WDIG Mobile, LLC	WDIG Mobile, LLC		www.dig.com
Western CLEC Corporation	Western CLEC Corporation		none
Western Wireless Corporation	Western Wireless Corporation		none
Wherify Wireless, Inc.	Wherify Wireless, Inc.		none
Wireless Alliance LLC	Wireless Alliance LLC		none
WWC Holding Co. - Cellular One (Western Wireless)	WWC Holding Co. - Cellular One (Western Wireless)		none
XE Mobile 55, LLC	XE Mobile 55, LLC		www.xemobile.com
YMAX Communications Corp.	YMAX Communications Corp.		www.ymaxcorp.com