



BROADMAPSM
Beyond The Boundaries

Oregon Broadband Mapping Project: Product Release White Paper

Contact Name Manager: Bryan Conway
Contact Phone Number: 503-378-6200
Contact E-mail: bryan.conway@state.or.us

Submitted By: Kristin Rousseau
Contact E-mail: kristin.rousseau@broadmap.com

Product Specification: Fall 2011 NTIA Data Model
Product/Process: NTIA—October 1, 2011 Data Deliverable
Dataset Submission QC: NTIA—SBDD_CheckSubmission.py



BROADMAP
Beyond The Boundaries

Table of Contents

OVERVIEW	5
SUBMISSION SUMMARY	5
PROVIDER DETAILS	5
PROVIDER PARTICIPATION	5
COVERAGE AREA CHANGES	7
DATA CORRECTIONS.....	7
COMMUNITY ANCHOR INSTITUTION (CAI) DETIALS	8
OVERALL STATISTICS	8
CAI CHANGES	8
SUBMISSION RECEIPT	9
SUBMISSION RECEIPT RESULTS	9
HIGH-LEVEL SUMMARY	10
DATA GATHERING	10
BROADBAND SERVICE AREAS, MIDDLE MILE AGGREGATION POINTS AND BROADBAND SERVICE OVERVIEW	10
COMMUNITY ANCHOR INSTITUTION (CAI)	10
DATA INTEGRATION PROCESS	11
DATA VALIDATION AND VERIFICATION.....	11
THIRD-PARTY DATA VERIFICATION	11
BROADBAND PROVIDER VALIDATION—PROVIDER PORTAL APPLICATION	11
CONFIDENCE VALUES	12
QUALITY CONTROL	12
DETAILED PROCESS REVIEW	13
PROVIDER OUTREACH	13
OUTREACH MATERIALS	14
OUTREACH PROCESS	14



BROADMAP
Beyond The Boundaries

DATA COLLECTION.....	15
DATA TRANSFER PROCEDURES	15
INITIAL DATA REVIEW AND QUALITY ASSURANCE	15
DATA INGESTION.....	15
DATA INGESTION OVERVIEW.....	15
POINT DATA.....	16
SUBSCRIBER LOCATION—ADDRESS DATA.....	16
SUBSCRIBER LOCATION—XY DATA	19
SUBSCRIBER LOCATION—GIS DATA	20
DSLAM OR CENTRAL OFFICE LOCATION—ADDRESS DATA	23
DSLAM OR CENTRAL OFFICE LOCATION—XY DATA	23
DSLAM OR CENTRAL OFFICE LOCATION—GIS DATA.....	23
BROADCAST TOWER LOCATION—ADDRESS DATA	28
BROADCAST TOWER LOCATION—XY DATA	28
BROADCAST TOWER LOCATION—GIS DATA	28
LINEAR DATA.....	35
TIGER® STREET SEGMENTS—LIST, SPREADSHEET OR GIS DATA	35
POLYGONAL DATA.....	39
COVERAGE AREA—PDF/JPG/OTHER IMAGE FORMAT	39
COVERAGE AREA—KML/KMZ	40
COVERAGE AREA—CAD DATA	41
COVERAGE AREA—GIS DATA	41
COMPACT POLYGON FROM SUBSCRIBER POINTS	42
CENSUS BLOCKS—LIST OR SPREADSHEET	44
CENSUS BLOCKS—GIS DATA	45
METADATA TRANSACTIONS	47
DATA PROCESSING	49
DATA PROCESSING OVERVIEW	49
WEIGHTED NOMINAL SPEED.....	50
SUBSCRIBER DATA SUPPLIED BY PROVIDER	50
VALUE SUPPLIED BY PROVIDER	50
MIDDLE MILE	50
BROADBAND COVERAGE TEMPLATE	51
VERIFICATION AND VALIDATION	52
PROVIDER VALIDATION—PROVIDER PORTAL/PDF MAP REVIEW	52
PROVIDER VERIFICATION—THIRD PARTY SOURCE REVIEW	52
ASSIGNING CONFIDENCE VALUES	53



BROADMAPSM
Beyond The Boundaries

COMMUNITY ANCHOR INSTITUTION (CAI) DATA.....	54
DATA COLLECTION	54
INSTITUTION DATA.....	54
COMMUNITY ANCHOR INSTITUTION (CAI) PORTAL UPDATES.....	55
PRODUCT EXTRACT.....	55
PYTHON SCRIPTS	55
PRODUCT EXTRACT PROCESS.....	55
PRODUCT STATISTICS	56
QUALITY ASSURANCE	57
QC SUITE	58
CONFIGURATION	58
LIBRARIES	58
QC SUITE	59
OTHER	59
PROCESS OPERATION AND MONITORING.....	59
BDIA PRODUCT CREATE	59
PRODUCT VALIDATION AND STATISTICS	62
PRODUCT EXTRACT DATA DELIVERY	63



BROADMAP
Beyond The Boundaries

OVERVIEW

This white paper highlights the **Submission Summary** for this deliverable, as well as describes the **Data Gathering**, **Data Integration**, **Data Validation and Verification** and **Quality Control** processes used to create the Broadband Mapping Project's October 1, 2011 data submission. To support varying levels of technical and program knowledge, both a **high-level summary** and a **detailed process review** are supplied.

SUBMISSION SUMMARY

PROVIDER DETAILS

PROVIDER PARTICIPATION

- Providers Included (listed by Provider and Holding Company name)

360networks
AboveNet Communications Inc.
Alyrica
AT&T Communications of the Pacific Northwest Inc
Axxis Communications
Bend Cable Communications, LLC
Broadband Cable Telecommunications LLC
Beaver Creek Telephone Company
Cal-Ore Communications Inc.
Canby Telephone Association
Cascade Networks, Inc.
Cascade Utilities
Casco Communications
CenturyLink
Chambers Cable
Charter Fiberlink OR - CCVII LLC
City of Sandy
Clear Creek Telephone & TeleVision
Clearwire
Colton Telephone
Comcast Cable Communications, LLC
Comspan Communications, Inc.
Country Vision Cable
Covad Communications Company
CP NW 1 LLC (Broadstripe)
Crestview Cable
Cricket Communications
Douglas Services, Inc/Douglas Cooperative
Eastern Oregon Telecom
Freewire Broadband

Frontier Communications of America
Gervais Telephone Company
Gorge Networks
Helix Telephone Company
Hughes Network Systems
Integra Telecom of Oregon Inc
J & N Cable Systems, Inc.
Level 3 Communications LLC
Lightspeed Networks Inc.
McMinnville Access Company (OnlineNW)
Molalla Communications
Monitor Cooperative Telephone Company
Monmouth Independence Networks (MINet)
Monroe Telephone Company
Mount Angel Telephone
Nehalem Telecommunications Inc (RTI)
North-State Telephone Co.
Oregon-Idaho Utilities Inc
Oregon Telephone Company
Oregonfast.net
Peoples Telephone Co
Pine Telephone Systems, Inc.
Pioneer Consolidated, Inc.
PocketiNet Communications, Inc.
Qlife
Quantum Communications
Qwest Communications Corp
Roome Telecommunications, Inc.
Rural Network

SCIO Mutual Telephone Assn.
SCS Communications and Security Inc
Sprint Nextel Corp
St Paul Telephone
Starband Communications Inc / Spacenet
Stayton Cooperative Telephone Co (SCTC)
Stephouse Holdings Company llc
T-Mobile
Tanager Telecommunucations (Sawnet)
TDS Telecom
Tillamook - CoastCom, Inc
Trans-Cascades Telephone
TW Telecom of Oregon LLC
Umpqua Indian Development (Rio Net)
Upward Access Support
Verizon Wireless
Warm Springs Telecommunications
Wave Division Holdings LLC
Webformix
Whiz to Coho Inc
WildBlue Communications Inc.
Wtechlink Wireless Broadband
XO Communications Services Inc.



BROADMAPSM
Beyond The Boundaries

- New Providers Since Last Data Submission
 - Hughes Network Systems – Satellite
 - Oregon-Idaho Utilities, Inc.
 - Silver Star Telecom LLC
 - Windwave Technologies, Inc.
- Non-Responsive Providers
 - Air Speed LLC
 - Bendtel Inc.
 - Eagle Telephone System, Inc.
 - Eaglecap.Net LLC
 - Hunter Communications Inc.
 - Nextnet Telecom Inc
 - Preferred Connections Inc NW
 - Tillamook Lightwave
 - Vertex Group Inc.
 - X5 PDX LLC
 - Yellow Knife Wireless
- Non-Cooperative Providers
 - Blue Mt TV Cable Co
 - Cogent Communications Group
 - Comspan Communications, Inc.
 - Gorge Ventures Inc
 - Meritel Group Inc
 - NextGen Internet Systems, Inc.
- Other Provider Changes
 - CenturyLink and Qwest have merged and submitted separate data for this round with the same FRN. Data was aggregated into one footprint and the Qwest provider name was removed.



BROADMAPSM
Beyond The Boundaries

COVERAGE AREA CHANGES

- Coverage Footprint Reductions/Map Refinement –
 - Douglas Services, Inc. (TT-50)
 - Integra – TT-10, 20 and 30
 - J & N Cable Systems, Inc. (TT-30)
 - Tanager – TT-70
- Coverage Footprint Expansion –
 - 360 Networks (USA) Inc. – Increase in Middle Mile
 - Ashland Fiber Network (TT-41 and TT-50)
 - Beaver Creek Telephone Company (TT-41 and TT-50)
 - Cableone (TT-41)
 - Cal-Ore Communications Inc. (TT-50)
 - Canby Telcom (TT-10, TT-20, TT-30, TT-50)
 - CenturyLink (TT-10)
 - Chambers Cable (TT-41)
 - Comcast (TT-40)
 - Covad Communications Company (TT-10, TT-20, TT-30)
 - Crestview Cable (TT-41)
 - Datavision Communications (TT-50)
 - Eastern Oregon Telecom (TT-10)
 - Frontier Communications Northwest Inc. (TT-10)
 - Integra Telecom (TT-10, TT-20, TT-30)
 - LS Networks (TT-30 and TT-50)
 - Mount Angel Telephone Company (TT-10)
 - New Edge Network (TT-30)
 - North-State Telephone Co. (TT-50)
 - Pine Telephone Systems, Inc. (TT-10 and TT-50)
 - QualityLife Intergovernmental Agency (TT-50)
 - Quantum Communications (TT-20, TT-30, TT-50)
 - SCIO Mutual Telephone (TT-10 and TT-50)
 - SawNet (TT-50)
 - Stayton Cooperative Telephone Company (TT10 and TT-50)
 - TW Telecom of Oregon LLC (TT-30 and TT-50)
 - Verizon Wireless (TT-80)
 - Wave Broadband (TT-41)
 - XO Communications Services, Inc. (Affiliated Entity) (TT-30)

DATA CORRECTIONS

- Comcast coverage data included in the spring data submission did not represent its complete coverage area, which was corrected with receipt of census block data from Comcast. Coverage has been validated by provider for dataset 4 submission.



BROADMAP
Beyond The Boundaries

COMMUNITY ANCHOR INSTITUTION (CAI) DETAILS

OVERALL STATISTICS

Community Anchor Institution - Categories	Overall Count	Broadband Subscriber (1 or 2)	Trans Tech	Advertised Speed Down	Advertised Speed Up
Category 1 - School K through 12	1616	359	349	318	318
Category 2 - Library	189	185	185	177	177
Category 3 - Medical/Healthcare	342	12	9	5	5
Category 4 - Public Safety	1135	238	114	65	65
Category 5 - Universities/Colleges	69	38	37	34	34
Category 6 - Other: Government	227	43	38	34	34
Category 7 - Other: Non-Government	19	3	1	1	1
Total	3597	878	733	634	634

CAI CHANGES

- The overall inventory was reviewed and updated to include institutions that were previously missed or that are new and to remove or add institutions to correctly represent categories 6 or 7 as defined by Oregon.
- Additional broadband attribution was collected and mapped mainly for Schools and Libraries; although broadband attribution improved within all categories.
- Another change was the inclusion of CAIDs to the CAI Inventory for Category 1: K-12 Schools, Category 2: Libraries and Category 5: Colleges, which were extracted from the three databases communicated by NTIA. These databases are as follows:
 - For K-12 institutions (CAI type 1) please add the NCES ID CCD ID value found here:
<http://nces.ed.gov/ccd/bat/>
 - For Higher Education (CAI type 5) please add the NCES IPEDS ID value found here:
<http://nces.ed.gov/ipeds/datacenter/>
 - For Libraries (CAI type 2) please. Combine (do not add) "FSCSKey" and "FSCs_SEQ" from the "puout08av2000" file and place them here:
<http://harvester.census.gov/imls/data/pls/index.asp> (FYI the LIBID is your state's unique ID for libraries)



BROADMAPSM
Beyond The Boundaries

SUBMISSION RECEIPT

SUBMISSION RECEIPT RESULTS

- Attached are the results from the NTIA data submission receipt quality script.



OR_2011_10_01.txt

- Error Report
 - The only item flagged in the submission receipt output is the following error, which has been verified as containing correct entries within the data submission.
 - Field Check: FAILED CAInstitutions_TRANSTECH has 2679 UNEXPECTED VALUES for query: TRANSTECH <> 0 AND TRANSTECH <> 10 AND TRANSTECH <> 20 AND TRANSTECH <> 30 AND TRANSTECH <> 40 AND TRANSTECH <> 41 AND TRANSTECH <> 50 AND TRANSTECH <> 60 AND TRANSTECH <> 70 AND TRANSTECH <> 71 AND TRANSTECH <> 80 AND TRANSTECH <> 90 AND TRANSTECH <> 0
 - This was flagged due to an inconsistency between the data model and the submission receipt script, which has also been communicated by other Grantees on PBWorks.

Hyperlink to Grantee Workspace in which the same issues were identified by other Grantees:

<https://sbdd-granteeworkspace.pbworks.com/w/page/42442088/Data%20Model%20Issues-June2011>



BROADMAPSM
Beyond The Boundaries

HIGH-LEVEL SUMMARY

DATA GATHERING

BROADBAND SERVICE AREAS, MIDDLE MILE AGGREGATION POINTS AND BROADBAND SERVICE OVERVIEW

The collection of Broadband Service Areas, Middle Mile Aggregation Points and Broadband Service Overview information is handled through the following Provider Outreach Process:

- Build and maintain an inventory of Broadband providers through research and State inputs.
- Update provider material that describes the data requirements and logistics for data transfer.
- Update Non-Disclosure Agreement (NDA) for use in project, where applicable.
- Maintain multiple protocols for the provider to submit data, including Secure File Transfer Protocol (SFTP) technology when desired.
- Conduct one-on-one informational discussions with each provider to communicate the following:
 - Requirements of this project;
 - Broadband data required to support the product data model;
 - Submission protocols available;
 - Capability to validate how the supplied data is aggregated.
- Download/receive provider data.
- Establish a repeatable process with provider. Maintain provider communication, transaction and data handling records throughout the project (dates contacted, data received, etc.).

COMMUNITY ANCHOR INSTITUTION (CAI)

The collection of CAI information is handled through the following CAI Collection Process:

- Collect and maintain an inventory of current CAIs through Grantee input and data mining,
- Collect and maintain CAI inventory attribution through anchor institution input using a web-based CAI portal, CAIID databases and state agencies. Upload data from the CAI portal to Core Database for standardization to NTIA data model, where needed.
- Perform internal data cleansing, such as removing duplicate records, identifying gaps or errors in broadband attribution and verifying category.
- Geocode CAI locations.
- Translate Core Database data to deliverable-ready format.
- Continued dialog with Grantee on accuracy of inventory and the collection of broadband attribution from non-responsive institutions.



BROADMAP
Beyond The Boundaries

DATA INTEGRATION PROCESS

The data integration and processing mechanisms currently used allow for multiple types of inputs and result in a standardized output that meets the NTIA deliverable requirements. This flexible process supports data model changes and project-requested enhancements.

- Receive inputs from providers via submission protocols; upload into Sourcing Database and catalog with provider information.
- Review provider-supplied data for completeness and for potential discrepancies that require resolution prior to processing and flag as necessary.
- Categorize input into data-type category (addresses, block lists, paper maps, etc.).
- Standardize input based on data type within Staging Database.
- Create Compact Polygons (CP)—(internal methodology for generating area-based feature for coverage in Staging Database).
- Apply broadband attribution to CP; apply metadata to CP.
- Perform quality analysis of the CP against the source supplied to identify any completeness or accuracy issues.
- Request additional information from the provider if elements of coverage are missing or contain discrepancies. This is a second manual quality check to ensure data is complete.
 - Process coverage area to build the required NTIA data model layers.
- Process CAI data input into internal standardized format, as discussed above in the [Community Anchor Institution \(CAI\) subsection](#), based on NTIA and State-level requirements.

DATA VALIDATION AND VERIFICATION

Following the creation of the product, process steps within Data Validation and Verification occur. To ensure the data collected and processed is as accurate and comprehensive as possible, provider validation and internal verification activities are employed. After the initial mapping of providers' coverage areas and serviceability claims, additional reviews are performed using the methods described in the subsections below ([Third-Party Data Verification](#), [Broadband Provider Validation](#), [Confidence Values](#)).

THIRD-PARTY DATA VERIFICATION

The coverage is visually and programmatically compared against third-party data. Pitney Bowes and American Roamer data are used in cases where a coverage area is questionable. All anomalies identified during this analysis are reviewed with the providers.

BROADBAND PROVIDER VALIDATION—PROVIDER PORTAL APPLICATION

Providers are trained on and requested to use a secure interactive web application to review their current coverage area(s) and supporting broadband attribution and validate their data or submit change requests to update their data. All provider change requests go through the [Data Integration Process](#) and are reviewed with the provider to complete validation.



BROADMAPSM
Beyond The Boundaries

CONFIDENCE VALUES

All verification, validation and manual quality review results are tracked by provider/technology type and stored and maintained within a **Validation table**. A confidence value is assigned, based on internal assessments of the collected information, to highlight the provider coverage areas and/or attributions that would benefit from further investigation and/or enhancements.

QUALITY CONTROL

Following collection, processing and analysis of the provider and CAI data, the product is checked manually and algorithmically against the NTIA data model. Some of the items included within these checks are:

- Format correctness;
- Table and field structure;
- Valid values, including default values, where applicable;
- Geographic extent and topology errors.

Prior to data submission, another quality control script supplied by NTIA is run. This script, SBDD_CheckSubmission.py, creates an output in text form that is required to be submitted along with the final deliverable. All errors must come up clean, unless otherwise specified by NTIA. Exceptions to the script as noted by NTIA on the SBDD Workspace on 03/25/11 can be found at the following link: <https://sbdd-granteeworkspace.pbworks.com/w/page/38218329/CheckSubmissionExceptions>


- Longitude values for States outside the lower 48 (any table);
- CAI results for Transtech, MaxAdUp, MaxAdDown if BBService is “No” or “Unknown”;
- Overview MaxAdDown, MaxAdUp if 100% of record-level data has MaxAdDown or MaxAdUp populated.



BROADMAP
Beyond The Boundaries

DETAILED PROCESS REVIEW

A detailed review of the data collection, integration and quality control points within the broadband data gathering and mapping process are discussed in the subsections that follow. In addition, a diagram showing the overall process can be seen below.



PROVIDER OUTREACH

For the October 2011 data submission, an e-mail notification was sent to all providers with supporting deliverable dates. The providers mainly used the Provider Portal web application to submit changes to and/or validate their current coverage area(s).

In support of the data collection effort, providers that did not timely respond to the outreach were contacted by phone.



BROADMAPSM
Beyond The Boundaries

OUTREACH MATERIALS

The original provider packet sent via e-mail to the providers included the following documents and files:

- Letter from the State inviting them to participate in the program;
- Copy of the Non-Disclosure Agreement (NDA);
- Copy of the Mapping NOFA from the NTIA;
- Copy of the NOFA Clarification from the NTIA;
- Broadband service address example file in CSV format;
- Word document describing service address example file;
- Broadband service block example file in CSV format;
- Word document describing service block example file;
- Broadband service street example file in CSV format;
- Word document describing service street example file;
- Broadband subscriber example file in CSV format;
- Word document describing subscriber example file;
- Broadband wireless coverage area sample shapefile;
- Word document describing wireless coverage area sample shapefile;
- Instructions for downloading, installing and using the WinSCP SFTP application.

OUTREACH PROCESS

The provider outreach process is comprised of the following general steps:

- Send the provider package and introduction letter to the main point of contact for the provider.
- Follow up with e-mail and telephone to verify that the main point of contact is correct.
- If necessary, discuss the NDA further and resolve any redlines.
- Once the correct primary contact is established, set up a telephone call, if necessary, to learn more about the provider's offerings and direct them to the appropriate outreach materials.
- If providers are unable to be contacted (non-responsive) or indicate that they are not interested in participating (non-cooperative), mark them as such on the provider tracking sheet. These providers will be escalated to the State for further action.
- As the providers are collecting the required data, provide instructions on downloading, installing and using the WinSCP SFTP application, if required.
- Arrange with the providers to transfer the data in whatever way they are comfortable: some providers will find regular email acceptable; others will want to use the SFTP application.
- After data is received and reviewed, it may be necessary to contact a provider for clarification or to address incomplete datasets. In the interest of building and maintaining relationships, care is given not to push the provider but to work with it to obtain accurate data in the best possible format.



BROADMAP
Beyond The Boundaries

DATA COLLECTION

DATA TRANSFER PROCEDURES

There are three primary ways data is collected from providers. These are:

- Secure FTP (SFTP) using the WinSCP application;
- Regular e-mail;
- Mail.

INITIAL DATA REVIEW AND QUALITY ASSURANCE

The initial data review and quality assurance process consists of the following general steps:

- 1) Access the data from the SFTP site or e-mail.
 - a. If e-mailed, place copy of original dataset in the appropriate provider folder on the SFTP site.
- 2) Place copy of raw data on local computer in a working directory.
- 3) Review data and determine course of action based on type of data received.
- 4) Ensure data is complete and contact provider to address any gaps.

NOTE:

The goal is to get as many providers as possible to provide subscriber address data in the correct format. Obviously, this will not be possible with all providers so we will continue to have to process various types of provider-supplied data.

DATA INGESTION

DATA INGESTION OVERVIEW

The following subsections outline the process steps taken based on the type of input supplied by the data provider:

- **Point Data:**
 - Subscriber location;
 - DSLAM location;
 - Central Office location;
 - Broadcast Tower location.
- **Linear Data:**
 - TIGER® street segments.
- **Polygonal Data:**
 - Census Blocks;
 - Coverage Area.

Overall, the process is geared toward taking the provider data supplied and creating polygon shapes to append to the bb_cov feature class. The bb_cov feature class is the interim dataset that is then processed using the makeDeliverable.py Python script to create the MapConnect™ data layers that will be delivered to the State and, ultimately, to the NTIA. Detailed instructions used in this process can be found in the subsections below.



BROADMAP
Beyond The Boundaries

POINT DATA

SUBSCRIBER LOCATION—ADDRESS DATA

In the event that the data provider supplies subscriber address data, the steps are as follows:

- 1) First, convert the address data to a clean Excel spreadsheet in an appropriate address data format.
 - a. Usually, this has the following columns: street address (number, pre-directional, pre-modifier, street name, street type, post-directional and post-modifier concatenated), city, state, ZIP.
- 2) Configure the ArcGIS® geocoding tool to use the TIGER® 2009 streets dataset.
 - a. In ArcCatalog®, create a new Address Locator by right-clicking in the white space of the appropriate directory and selecting **New>Address Locator** from the dropdown menu.
 - b. Select **US Streets with Zone** and click **OK**.

NOTE:


It is likely that multiple Address Locators will have to be set up to handle the variety of provider address data received.

- c. Navigate to the **TIGER Streets 2009** file and click **OK**.
- d. Fill in the dialog box, as shown below:




BROADMAP
Beyond The Boundaries

- e. Click **OK**.
- 3) Open ArcMap® and add the Excel spreadsheet with the address information.
- 4) Right-click on the Excel spreadsheet and select **Geocode Addresses** from the dropdown menu.
- 5) Select the appropriate address locator by clicking **Add...**, then **OK**.




- 6) Fill out the **Geocode Addresses** dialog box, as shown below:




- 7) Geocode the list in batch mode using the geocode service set up in **Step 2** above, accepting all the default parameters.
- 8) Review results. See example below.



BROADMAP
Beyond The Boundaries



- 9) Adjust geocoding parameters accordingly and repeat batch to resolve issues.
- 10) Manually geocode unmatched addresses until target hit rate achieved, generally 90%.
- 11) Visually inspect the data, as shown below:



- 12) Follow the steps detailed in [Subscriber Location—GIS Data](#) below.



BROADMAP
Beyond The Boundaries

SUBSCRIBER LOCATION—XY DATA


If the provider supplies a list of subscriber data with accompanying XY data such as latitude and longitude, the steps are as follows:

- 1) Refine the format in Excel so that the data can be opened easily using ArcMap®.
 - a. Remove all font color, highlighting, cell colors and borders, clean up column headers and make certain there are no merged cells.
 - b. Make certain that XY locations are in decimal degrees.
 - (i.) To convert from degrees, minutes, seconds (39° 26' 45.67") to decimal degrees, use the following formula: $DD + (MM/60) + (SS.SSS/3600)$.

NOTE:

If XY locations from some other coordinate system are provided, you can use those in the process below but you must know what the coordinate system is.

- 2) Open the Excel worksheet in ArcMap®.
- 3) From the menu bar, select **Tools>Add XY Data...**



- 4) Supply the appropriate fields for the X and Y coordinates, choose the appropriate coordinate system and click **OK**.
- 5) Results are an event layer, not a true spatial layer. Export the data by right-clicking the event layer and selecting **Data>Export Data...** from the dropdown menu.
- 6) Follow the steps detailed in [Subscriber Location—GIS Data below](#).



BROADMAP
Beyond The Boundaries

SUBSCRIBER LOCATION—GIS DATA

If the provider supplies subscriber location in GIS format, the only process step is to load that data into the appropriate data schema and it will be ready for processing.

- 1) First, load the data into the Point Address database schema (please see Appendix D for an example of the Point Address database schema.) using an empty feature class in that schema.
- 2) In ArcCatalog®, right-click on the empty feature class and select **Load** from the dropdown menu.
- 3) Navigate to the provider address GIS dataset and then map the attribute fields accordingly, as shown below:

The Simple Data Loader dialog box is shown with the following table of field mappings:


Target Field	Matching Source Field
street_id [int]	<None>
side [string]	<None>
feature_id [int]	<None>
point_type [short int]	<None>
add_house_num [string]	BLDG_NUM [string]
add_pre_dir [string]	PRE_DIR [string]
add_pre_type [string]	<None>
add_name_body [string]	STREET_NM [string]
add_suf_type [string]	SUF_TYPE [string]
add_suf_dir [string]	SUF_TYPE [string]

Buttons: Reset, < Back, Next >, Cancel

- 4) Once you have successfully loaded the provider address data into the temporary database with the correct schema, you now will append that data to the overall Point Address database.
- 5) In ArcToolbox®, use the **Append** command (**Data Management Tools>General> Append**) to add the features into the overall Point Address database, as shown below:



BROADMAP
Beyond The Boundaries




- 6) Since the data is already in the Point Address database schema, there is no need to alter the Field Map in the Append tool.
- 7) After appending, calculate metadata reflecting geometry source and representation values.
- 8) Break provider-specific points into separate county feature classes and perform the following steps per county feature class:
 - a. Within ArcGIS®:
 - (i.) Summarize download and upload speeds [first,last] to determine all speeds available for county.
 - (1) This will save as a DBF table. Keep track of location for future reference.
 - (ii.) Buffer county address point featureclass to 150'.
 - (1) During buffer command, dissolve on ad_down; ad_up; provider; dba; frn; tt; all metadata fields; stctyfips. Save as.... county_fastestdown_fastestup.
 - (2) Example using Qwest data: boulder_40128_20128, where boulder=county; 40128=ad_down; 20128=ad_up.


NOTE:

These attribute fields are specific to the Point Address database.

- (iii.) Select the features that represent the lowest speeds.
- b. Using XtoolsPro (<http://www.xtoolspro.com/>):
 - (i.) In the XTools Pro toolbar, select **XTools Pro>Layer Operations>Erase Features**.
 - (ii.) Use the same feature class for Input and Overlay.
 - (iii.) Check **Use selected features** on the **Input** feature, as shown below.
 - (iv.) Repeat and erase slowest speeds one speed at a time. Save each new feature class as the next slowest speed, using the same naming convention as shown in **a.(ii.)(1)** above. A general example is shown below:



- c. Return to ArcGIS®:
- (i.) Edit/delete speeds from the attribution table of each feature class, so each remaining feature class has only one speed value.
 - (ii.) Merge individual speed feature classes using the **Merge** command in ArcToolbox® (**Data Management Tools>General>Merge**). The dialog box is shown below:



- (iii.) Merge individual county feature classes using the **Merge** command in ArcToolbox (**Data Management Tools>General>Merge**).
- (iv.) Since the county files are all in the same schema, DO NOT alter the Field Map portion of the command interface.



BROADMAP
Beyond The Boundaries

- (v.) When all the county files are merged into one dataset, use the **Append** command in ArcToolbox® (**Data Management Tools>General>Append**) to add the features to the bb_cov interim dataset. Use the **Field Map** portion of the **Append** tool to map the appropriate field values to their corresponding fields in the bb_cov feature class.

DSLAM OR CENTRAL OFFICE LOCATION—ADDRESS DATA

In the event that the provider supplies DSLAM (digital subscriber line access multiplexer) or Central Office address data, the steps are as follows:

- 1) Follow the process for geocoding points in **Subscriber Location—Address Data** above.
- 2) Follow the steps detailed in **DSLAM or Central Office Location—GIS Data** below.

DSLAM OR CENTRAL OFFICE LOCATION—XY DATA


In the event that the provider supplies DSLAM (digital subscriber line access multiplexer) or Central Office XY data, the steps are as follows:

- 1) Follow the process for creating points from XY data in **Subscriber Location—XY Data** above.
- 2) Follow the steps detailed in **DSLAM or Central Office Location—GIS Data** below.

DSLAM OR CENTRAL OFFICE LOCATION—GIS DATA

In the event that the provider supplies DSLAM (digital subscriber line access multiplexer) or Central Office GIS data, the steps are as follows:


- 1) Buffer the DSLAM/Central Office points feature class.
 - a. Add the point feature class to ArcMap®.
 - b. Open the ArcToolbox® and go to **Analysis Tools>Proximity>Buffer**.
 - c. Set the buffer distance to 5 miles.
 - d. Set the dissolve type to **ALL**.
 - e. Name the output feature class.
 - f. Typical **Buffer** tool is shown below:





BROADMAP
Beyond The Boundaries


- g. Click **OK**.
- 2) Use the resulting buffer feature class to clip the TIGER® street layer:
 - a. Add TIGER® street layer to ArcMap®.
 - b. Open the ArcToolbox® and go to **Analysis Tools>Extract>Clip**.
 - c. Complete the dialog box as shown below:



- d. Click **OK**.
- 3) Using ArcCatalog® and within the file geodatabase:
 - a. Right-click and create a new Feature Dataset.
 - (i.) For the Feature Dataset settings:
 - (1) Name the feature dataset accordingly.
 - (2) Select horizontal coordinate system by importing the coordinate system associated with the clipped TIGER® street layer by selecting **Import** and navigating to the location of that feature class.
 - (3) No vertical coordinate system needed.
 - (4) Leave all x,y,z,m values at default.
 - (5) Click **Finish**.
 - 4) Import previously created street feature class into new **Feature Dataset**.
 - 5) Right-click **Feature Dataset** and create new Network Dataset—accept all default setting for the Network Dataset.


NOTE:

The Network Analyst extension must be turned on.


- 6) In ArcMap® turn on the **Network Analyst Toolbar** by going to **View>Toolbars>Network Analyst**.
- 7) Add the Network Dataset created in **Step 5** to ArcMap.
- 8) Using the **Network Analyst Toolbar** dropdown, create **New Service Area**.
- 9) Open the **Network Analyst Window** by selecting the  button. See below.




BROADMAP
Beyond The Boundaries




- 10) Right-click **Facilities** layer, select **Load Locations** and navigate to the DSLAM/Central Office facilities feature class.




- 11) Click **OK**.
- 12) Click the **Service Area Properties** button .
- 13) For the following tabs, change the following properties:
- Polygon Generation** tab:
 - Select **Merge by break value**.
 - Also disable the **Trim Polygons** option.
 - Analysis Settings** tab—using and converting the specified DSLAM buffer distance from feet to meters—input buffer distance value in meters into the **Default Breaks** location.
 - Generally, 18,000 feet (5486 meters) from DSLAM or Central Office location is used as the buffer distance. See below.



BROADMAP
Beyond The Boundaries



c. Click **OK**.

- 14) On the **Network Analyst Toolbar**, click the **Solve** button  to create service area polygons.
- 15) Right-click on the created service area polygon in the layer list, and select **Data>Export Data** from the dropdown list.
- 16) Export to a feature class in the file geodatabase you created earlier.
- 17) In ArcCatalog®, create an empty feature class with the schema of the bb_cov feature class and load the feature class created in [Step 16](#) into it.
 - a. Right-click on the empty feature class, select **Load>Load Data** from the dropdown menu and navigate to the location of the service area feature class.
 - b. Click the **Add** button, then click **Next**.
 - c. Accept the defaults and click **Next**.
 - d. DO NOT attempt to map any fields, as shown below:



Simple Data Loader

For each target field, select the source field that should be loaded into it.

Target Field	Matching Source Field
ProvName [string]	<None>
DBAName [string]	<None>
FRN [int]	<None>
GeogUnit [string]	<None>
GeogUnitID [string]	<None>
TransTech [short int]	<None>
MaxAdvDown [short int]	<None>
MaxAdvUp [short int]	<None>
ARPU [float]	<None>
SWNomSpeed [float]	<None>

Reset

< Back Next > Cancel

e. Click **Next**, then **Next** again, then **Finish**.

18) In ArcToolbox®, go to **Data Management Tools>General>Append**.

19) Append the formerly empty feature class to bb_cov, completing the dialog box, as shown below:

Append

Input Datasets

C:\Working\Broadband\ProviderData\Columbine\Columbine.gdb\service_area_bb...

Target Dataset

C:\Working\Broadband\ProviderData\Columbine\Columbine.gdb\bb_cov

Schema Type (optional)

TEST

Field Map (optional)

OK Cancel Environments... Show Help >>

20) Leave the **Schema Type** as **TEST**.

21) Click **OK**.

22) In ArcMap®, open bb_cov for editing and manually input associated attribution.



BROADMAP
Beyond The Boundaries

BROADCAST TOWER LOCATION—ADDRESS DATA

In the event that the provider supplies wireless broadcast tower location address data, the steps are as follows:

- 1) Follow the process for geocoding points in **Subscriber Location—Address Data** above.
- 2) Follow the steps detailed in **Broadcast Tower Location—GIS Data** below.

BROADCAST TOWER LOCATION—XY DATA

In the event that the provider supplies wireless broadcast tower location XY data, the steps are as follows:


- 1) Follow the process for creating points from XY data in **Subscriber Location—XY Data** above.
- 2) Follow the steps detailed in **Broadcast Tower Location—GIS Data** below.

BROADCAST TOWER LOCATION—GIS DATA

In the event that the provider supplies wireless broadcast tower location GIS data, the steps are as follows:

- 1) Download the required software (Radio Mobile) from the website:
<http://www.cplus.org/rmw/english1.html>
- 2) Install the software according to the standard directions, found here:
<http://www.cplus.org/rmw/download/download.php?S=1>
- 3) Open the application.
- 4) Load the broadcast tower location and elevation information by selecting **File>Unit properties**.

The following dialog box appears:




- 5) Add the information for all the towers supplied by the WISP data provider, including the elevation. If provider does not supply elevation, this information can be obtained from Google Earth.
 - a. If available, use the **Import** button to import a Google Earth KML of the tower locations.
- 6) Go to the National Map Seamless Server (<http://seamless.usgs.gov/>) and download elevation data sufficient to contain the tower locations.




BROADMAP
Beyond The Boundaries

- a. At least the 1/3" NED data is needed. Select this by clicking the **Download** button in the upper right of the website and checking the box next to **1/3" NED**.
- b. Zoom to the area of interest and use the **Download** tools to define the area to download:



- c. Click the **Modify Data Request** button to request the data in BIL_16INT format, not ESRI GRID, as shown below:



- d. Download the data and unzip it.
- 7) Select **File>Map Properties** to define the map.
- 8) Enter a latitude and longitude in the center of the tower locations.
- 9) Set the size (in pixels) and the size (in kilometers) of the map.
- 10) Set the directory path leading to the BIL elevation data just downloaded.
- 11) The dialog box is shown below:



BROADMAP
Beyond The Boundaries

Properties of ..\default.map

Centre
40°03'28.8"N 105°29'27.6"W
DN70GB
Latitude Longitude
40.058 -105.491
Use cursor position
World map
Select a city name
Enter LAT LON or QRA
Select a unit

Size (pixel)
Width(pixels) Height (pixels)
1000 1000
Size (km)
Width(km) Height (km)
100.00 100.00

Elevation data source
Drive or path Top layer
BIL c:\geodata\bil\boulder Browse...
None Browse...
None Browse...
None Browse...
None Browse...
Ignore missing files Bottom layer
Initialize matrix with elevation (m) 0


Extract
Cancel

Top Left
40°30'29"N
106°04'44"W
Top Right
40°30'29"N
104°54'11"W
Bottom Left
39°36'29"N
106°04'44"W
Bottom Right
39°36'29"N
104°54'11"W
Resolution
100.0 m/pixel
3.24 arcsecond

☐ Adjust units elevation
☐ Merge pictures
☒ Force gray scale

12) Click **Extract**.

13) The elevation data is rendered as a hill shade, as shown below:



14) Select **File>Network properties** from the main menu.

15) Create a new network and enter in the frequency range under the **Parameters** tab, as shown below:



Networks properties

Default parameters Copy Net Paste Net Cancel OK

List of all nets

- Nednet
- Jade
- Ouray
- COMobile
- Nednet**
- Net 6
- Net 7
- Net 8
- Net 9
- Net 10
- Net 11
- Net 12
- Net 13
- Net 14
- Net 15
- Net 16
- Net 17
- Net 18
- Net 19
- Net 20
- Net 21
- Net 22
- Net 23
- Net 24
- Net 25

Parameters Topology Membership Systems Style

Net name: Nednet

Surface refractivity (N-Units): 301

Ground conductivity (S/m): 0.005

Relative ground permittivity: 15

Polarization: ☒ Vertical ☐ Horizontal

Mode of variability: ☒ Spot % of time: 50 ☐ Accidental % of locations: 50 ☐ Mobile % of situations: 70 ☐ Broadcast

Climate: ☐ Equatorial ☐ Continental sub-tropical ☐ Maritime sub-tropical ☐ Desert ☒ Continental temperate ☐ Maritime temperate over land ☐ Maritime temperate over sea

16) Leave all the other values as they appear, and select the **Systems** tab.

17) Create enough systems to cover all the varieties of equipment in the provider network. This will include the antenna type, height and line loss, as shown below:

Networks properties

Default parameters Copy Net Paste Net Cancel OK

List of all systems

- Omni**
- 60
- 120
- System 4
- System 5
- System 6
- System 7
- System 8
- System 9
- System 10
- System 11
- System 12
- System 13
- System 14
- System 15
- System 16
- System 17
- System 18
- System 19
- System 20
- System 21
- System 22
- System 23
- System 24
- System 25

Parameters Topology Membership **Systems** Style

01 Select from Radiosys01.dat

System name: Omni

Transmit power (Watt): 100 (dBm): 50

Receiver threshold (µV): 1 (dBm): -107

Line loss (dB): 1 (Cable+cavities+connectors)

Antenna type: omni.ant View

Antenna gain (dBi): 15 (dBd): 12.85

Antenna height (m): 9 (Above ground)

Additional cable loss (dB/m): 0 (If antenna height differs)

Add to Radiosys01.dat Remove from Radiosys01.dat



BROADMAP
Beyond The Boundaries

- 18) Now click on the **Membership** tab, and assign the individual towers to their respective systems, providing the azimuth for non-omnidirectional antennas, as shown below:

The 'Networks properties' dialog box is shown with the 'Membership' tab selected. On the left, a list of networks includes 'Nednet', 'Jade', 'Ouray', 'COMobile', and 'Nedernet' (which is selected). In the center, a list of units includes 'Althea', 'Athena', 'Caribou', 'Chipeta', 'Franklins', 'Horizon-E', 'Horizon-W', 'Littleraven', 'Manzanala-H', 'Manzanala-V', 'Moonstone', 'Pirata', 'Terrapin', 'Tobago', 'Turtle', and 'Wapiti'. On the right, the 'Member of Nedernet' section shows 'Role of Athena' set to 'Command' and 'System' set to '60'. The 'Antenna height (m)' section has 'System' selected with a value of '9', and 'Other' is set to '0.5'. The 'Antenna direction' section has 'Fixed (*)' selected, with 'Azimuth (*)' set to '90' and 'Elevation angle (*)' set to '0'. A 'View pattern' button is at the bottom right.


- 19) Click **OK**.
20) Select **Tools>Radio Coverage>Combined Cartesian** from the main menu.
21) Complete the dialog box as shown below, providing the **Maximum Range** from the highest tower beam radius supplied by the provider.
22) Set the **Pixel Size** at 5 (experiment depending on the area covered to get the right level of granularity), as shown below:

The 'Combined cartesian Radio coverage' dialog box is shown. On the left, a list of fixed units includes 'Althea', 'Athena', 'Caribou', 'Chipeta', 'Franklins', 'Horizon-E', 'Horizon-W', 'Littleraven', 'Manzanala-H', 'Manzanala-V', 'Moonstone', 'Pirata', 'Terrapin', 'Tobago', 'Turtle', and 'Wapiti'. In the center, the 'Wapiti' unit is selected, showing 'Antenna pattern' as 'omni.ant', 'Antenna height (m)' as '9', and a 'Backcolor' button. On the right, the 'Mobile unit' is 'Althea', 'In network' is 'Nedernet', and 'Use network antenna settings' is checked. The 'Maximum range (km)' is set to '7.62'. The 'Link Direction' section has 'Mobile Rx' selected. The 'Signal range to draw' section has 'S-Unit' selected, 'Best unit' is checked, and 'From (>=)' is set to '5'. The 'Draw size (pixels)' is set to '5'. A 'Draw' button is at the top right.

- 23) Set the **Signal range to draw** to S-Unit and type 5 in the **From (>=)** box.
24) Click on **Draw**. See below.



BROADMAP
Beyond The Boundaries



- 25) Save the resulting image as a TIF by selecting **File>Save Picture as**.
- 26) Open ArcMap® and load the BIL elevation data you used in Radio Mobile.
- 27) Load the TIF image you created and georeference it using the corners of the BIL data.
 - a. The corners of the data can be seen in the TIF image.
- 28) Follow the georeferencing directions from the [Coverage Area—PDF/JPG/Other Image Format](#) section below.
- 29) Use the **Georeferencing Toolbar** to **Update the Georeferencing** for the TIF dataset.
- 30) In ArcToolbox®, select **Data Transformations>From Raster>Raster to Polygon** and input the georeferenced TIF you just created, as shown below:
- 31) Open the resulting polygon feature class for editing using the **Editing** toolbar in ArcMap® and clean up as necessary.
- 32) In ArcCatalog®, create an empty feature class with the schema of the bb_cov feature class and load the feature class created above into it.
 - a. Right-click on the empty feature class, select **Load>Load Data** from the dropdown menu and navigate to the location of the service area feature class.
 - b. Click the **Add** button, then click **Next**.
 - c. Accept the defaults and click **Next**.
 - d. DO NOT attempt to map any fields, as shown below:



Simple Data Loader

For each target field, select the source field that should be loaded into it.

Target Field	Matching Source Field
ProvName [string]	<None>
DBAName [string]	<None>
FRN [int]	<None>
GeogUnit [string]	<None>
GeogUnitID [string]	<None>
TransTech [short int]	<None>
MaxAdvDown [short int]	<None>
MaxAdvUp [short int]	<None>
ARPU [float]	<None>
SWNomSpeed [float]	<None>

Reset

< Back Next > Cancel

e. Click **Next**, then **Next** again, then **Finish**.

33) In ArcToolbox®, go to **Data Management Tools>General>Append**.

34) Append the formerly empty feature class to bb_cov, completing the dialog box, as shown below:

Append

Input Datasets

C:\Working\Broadband\ProviderData\Columbine\Columbine.gdb\service_area_bb...

Target Dataset

C:\Working\Broadband\ProviderData\Columbine\Columbine.gdb\bb_cov

Schema Type (optional)

TEST

Field Map (optional)

OK Cancel Environments... Show Help >>

35) Leave the **Schema Type** as **TEST**.

36) Click **OK**.

37) In ArcMap®, open bb_cov for editing and manually input associated attribution.




BROADMAP
Beyond The Boundaries

LINEAR DATA

TIGER® STREET SEGMENTS—LIST, SPREADSHEET OR GIS DATA

In the event that the provider supplies TIGER® street segments in list or spreadsheet format, the steps are as follows:

- 1) Join TIGER® road segments to 2000 census blocks feature class using one of two methods based on how the data is provided:
 - a. If the TIGER® data is provided with a Census Block ID, then join the segments to the Census Block geometry based on that ID:
 - (i.) Load both datasets into ArcMap®;
 - (ii.) In the layer list, right-click on the 2000 census block feature class and select **Joins and Relates>Join**;
 - (iii.) In the dialog box, select the TIGER® road segments data and the proper attribute fields for joining, as shown below:



- (iv.) Click **OK**.
 - b. If the data provided is a list containing TLIDs, then join to the TIGER®/Line data using the TLID, and use a spatial join to associate the TIGER® segment with the coterminous block based on the block ID:
 - (i.) Load both datasets into ArcMap®;
 - (ii.) In the layer list, right-click on the 2000 census block feature class and select **Joins and Relates>Join**;
 - (iii.) Select **Join data from another layer based on spatial location** from the dropdown menu;
 - (iv.) Complete the dialog box, as shown below and click **OK**.




BROADMAPSM
Beyond The Boundaries

- 2) Export joined records into a temporary feature class.
- 3) If joined Census Block geometry is confined to one specific area, then dissolve blocks into one record. If joined Census Block geometry is distributed throughout a particular State, then dissolve sub-selections of census blocks for each county.
 - a. Use the County FIPS code to dissolve by county.
 - b. In ArcToolbox®, select **Data Management Tools>Generalization>Dissolve**.
 - c. Complete the **Dissolve** dialog box, as shown below:



BROADMAP
Beyond The Boundaries



- d. Click **OK**.
- 4) For each dissolved region, open the feature class for editing using the **Editing** tool in ArcMap® and remove unnecessary slivers and other small holes. For general guidance on editing features in ArcMap®, see http://webhelp.esri.com/arcgisdesktop/9.3/pdf/Editing_Tutorial.pdf
- 5) In ArcCatalog®, create an empty feature class with the schema of the bb_cov feature class and load the feature class created above into it.
 - a. Right-click on the empty feature class, select **Load>Load Data** from the dropdown menu and navigate to the location of the service area feature class.
 - b. Click on the **Add** button, then click **Next**.
 - c. Accept the defaults and click **Next**.
 - d. DO NOT attempt to map any fields, as shown below:



Simple Data Loader

For each target field, select the source field that should be loaded into it.

Target Field	Matching Source Field
ProvName [string]	<None>
DBAName [string]	<None>
FRN [int]	<None>
GeogUnit [string]	<None>
GeogUnitID [string]	<None>
TransTech [short int]	<None>
MaxAdvDown [short int]	<None>
MaxAdvUp [short int]	<None>
ARPU [float]	<None>
SWNomSpeed [float]	<None>

Reset

< Back Next > Cancel

- e. Click **Next**, then **Next** again, then **Finish**.
- 6) In ArcToolbox®, go to **Data Management Tools>General>Append**.
- 7) Append the formerly empty feature class to bb_cov, completing the dialog box, as shown below:

Append

Input Datasets

C:\Working\Broadband\ProviderData\Columbine\Columbine.gdb\service_area_bb...

Target Dataset

C:\Working\Broadband\ProviderData\Columbine\Columbine.gdb\bb_cov

Schema Type (optional)

TEST

Field Map (optional)

OK Cancel Environments... Show Help >>

- 8) Leave the **Schema Type** as **TEST**.
- 9) Click **OK**.
- 10) In ArcMap®, open bb_cov for editing and manually input associated attribution if necessary.




BROADMAP
Beyond The Boundaries


POLYGONAL DATA

COVERAGE AREA—PDF/JPG/OTHER IMAGE FORMAT

In the event that the provider supplies coverage area data in some image format such as PDF or JPG format, the steps are as follows:


- 1) If in PDF format, open in Adobe Acrobat and **Save As...** JPG format.
- 2) Open the JPG image in ArcMap®.
- 3) Add the required base map vector data for georeferencing.
 - a. This generally will be either the CDOT data or TIGER® data.
- 4) Change the coordinate system of the data frame to the desired end coordinate system.
- 5) Zoom to the general location of the JPG map image.
 - a. This is the location based on the vector data, not the JPG image itself. For example, if you know that the JPG image represents an area around the town of Limon, zoom to the town of Limon in your vector data.
- 6) Open the **Georeferencing** toolbar by selecting **View>Toolbars>Georeferencing** from the main menu bar.
- 7) Using the **Georeferencing** toolbar, select **Fit to Display**; results are shown below:



- 8) Use the **Control Point** button  to add control points to the map.
- 9) Use common points in the base dataset and the JPG image.
 - a. For example, find major street intersections, county/city boundaries, etc.
 - b. Try to distribute the points more or less in the four corners on the image for the best transformation.
- 10) Click on the location on the image first, then click on the corresponding location on the vector database map, as shown in the image below:




BROADMAP
Beyond The Boundaries



- 11) After placing each control point, the image transformation will update automatically.
- 12) Repeat until satisfied with the transformation.

NOTE:

The transformation may take up to four points, although sometimes only two are necessary.

- 13) When satisfied with the transformation, select **Update Georeferencing** from the **Georeferencing** toolbar dropdown.
 - a. This will create a “world” file (.jgw in the case of JPGs) in the same directory as the image file.
- 14) In ArcCatalog®, create a new polygon shapefile with the appropriate data schema for a provider coverage area, which can be found in Appendix D.
- 15) Add the shapefile to ArcMap®.
- 16) Using the **Editor** toolbar, select **Start Editing**. Set the **Task** to **Create New Feature**.
- 17) Use the **Sketch Tool**  to digitize a new coverage polygon using the coverage area outline from the georeferenced JPG and add the required attributes manually.
- 18) Repeat the above steps for all subscriber speed coverage areas provided.
- 19) Follow the steps detailed in **Coverage Area—GIS Data** below.


COVERAGE AREA—KML/KMZ

In the event that the provider supplies coverage area data in Google Earth KML or KMZ format, the steps are as follows:

- 1) Use a KML to SHP converter to translate file into an Esri® format.
- 2) <http://arcscripts.esri.com/details.asp?dbid=15603>
- 3) Download the script and follow the provided instructions for installing it in ArcToolbox®.
- 4) Double-click on the script in ArcToolbox® and navigate to the location of the KML file, as shown below:




BROADMAP
Beyond The Boundaries



- 5) Add the new shapefile to ArcMap®. Repeat for all KML files provided.
- 6) Follow the steps detailed in [Coverage Area—GIS Data](#) below.

COVERAGE AREA—CAD DATA

In the event that the provider supplies coverage area data in GIS format, the steps are as follows:

- 1) Transform the CAD dataset into an Esri® format.
- 2) http://webhelp.esri.com/arcgisdesktop/9.2/index.cfm?TopicName=Transforming_CAD_datasets
- 3) It may be necessary to contact the provider first to determine the coordinate system of the CAD data.
- 4) If the CAD data is not in a standard coordinate system, it may be necessary first to use ArcMap® to georeference the CAD data to a known coordinate system.
 - a) To do so, follow the instructions provided above in [Coverage Area—PDF/JPG/Other Image Format](#).
- 5) In ArcCatalog®, create a new polygon shapefile with the appropriate data schema for a provider coverage area, which can be found in Appendix D.
- 6) Add the shapefile to ArcMap®.
- 7) Using the **Editor Toolbar**, select **Start Editing**. Set the **Task** to **Create New Feature**.
- 8) Use the **Sketch Tool**  to digitize a new coverage polygon using the coverage area outline from the georeferenced CAD file and add the required attributes manually.
- 9) Follow the steps detailed in [Coverage Area—GIS Data](#) below.

COVERAGE AREA—GIS DATA

In the event that the provider supplies coverage area data in GIS format, the steps are as follows:

- 1) In ArcCatalog®, create an empty feature class with the schema of the bb_cov feature class and load the GIS feature class either created above or supplied by the provider into it.
 - a. Right-click on the empty feature class, select **Load>Load Data** from the dropdown menu and navigate to the location of the service area feature class.
 - b. Click on the **Add** button, then click **Next**.
 - c. Accept the defaults and click **Next**.
 - d. DO NOT attempt to map any fields, as shown below:



BROADMAP
Beyond The Boundaries

Simple Data Loader

For each target field, select the source field that should be loaded into it.

Target Field	Matching Source Field
ProvName [string]	<None>
DBAName [string]	<None>
FRN [int]	<None>
GeogUnit [string]	<None>
GeogUnitID [string]	<None>
TransTech [short int]	<None>
MaxAdvDown [short int]	<None>
MaxAdvUp [short int]	<None>
ARPU [float]	<None>
SWNomSpeed [float]	<None>

Reset

< Back Next > Cancel

- e. Click **Next**, then **Next** again, then **Finish**.
- 2) In ArcToolbox®, go to **Data Management Tools>General>Append**.
- 3) Append the formerly empty feature class to bb_cov, completing the dialog box, as shown below:

Append

Input Datasets

C:\Working\Broadband\ProviderData\Columbine\Columbine.gdb\service_area_bb...

Target Dataset

C:\Working\Broadband\ProviderData\Columbine\Columbine.gdb\bb_cov

Schema Type (optional)

TEST

Field Map (optional)

OK Cancel Environments... Show Help >>

- 4) Leave the **Schema Type** as TEST.
- 5) Click **OK**.
- 6) In ArcMap®, open bb_cov for editing and manually input associated attribution, if necessary.

COMPACT POLYGON FROM SUBSCRIBER POINTS


- 1) Geocode address list using latest **State Composite Locator**.
- 2) Verify that your geocoded file has only one TT (Technology Type). If not, export individual geocoded layers for each Technology Type.
- 3) For each TT, check for differences in speed values or speed tiers and create separate layers for each speed value/tier.



BROADMAP
Beyond The Boundaries

- 4) Clean your geocoding results: remove any points that geocode to accuracy levels below ZIP+4 (ZIP centroids, carrier route centroids, etc). Also, verify that outliers with acceptable accuracy levels are legitimate, i.e., fall in correct city and Zip.
- 5) Perform spatial join between county polygons (using stcnfyips field) and the cleaned geocoded subscriber points in order to carry the county name and stcnty fips.
- 6) Summarize the number of subscribers by county and use the subscriber counts by county to populate the Rate Tier table.
- 7) Un-join the county data from the geocode subscribers list.
- 8) Create Compact Polygon using cleaned geocoded layer or sub-selection of XtoolsPro—ConvexHull-DetailedHull option. A sub-selection of geocoded points will be used in areas where more than one polygon will need to be created for one provider's service area.
- 9) Evaluate output Hull carefully, looking for areas that should not be covered by hull polygon.
 - a. If it is determined that an area or areas should not be represented in coverage area, manually reshape hull polygon until coverage area is adequate.
 - b. When not obvious and as a general rule, manually resolve compact polygon when the distance between the subscriber points used to define the outer boundary of the compact polygon exceeds 5 miles . When reshaping the hull polygon, snap to the outermost geocoded points. See the three figures below for examples.

Compact Hull: Manual Resolution Required





BROADMAP
Beyond The Boundaries

Compact Hull: Manual Resolution Required



Compact Hull: After Manual Resolution



- 10) To attribute the compact polygon, perform a spatial join where your Target Feature Class is the compact polygon and the Join Feature Class is your geocoded point layer. Export compact hull with joined attributes and name file appropriately.
- 11) Append attributed compact polygon to Broadband TT template Feature Class and, if required, manually input any provider attribution that may not have carried over in the append process.
- 12) Intersect compact polygon with county boundaries to create unique records by county and use the state-county-fips field to populate stcty_fips field. Also use the county name field to populate the BBCov_Name field.
 - a. Exception: where a provider's coverage is distributed throughout more than one area of any given county where the BBCov_Name should be populated using an appropriate city or other logical name based on geographical location.
- 13) Export/load into appropriate BB TT model dataset.

CENSUS BLOCKS—LIST OR SPREADSHEET

In the event that the provider supplies census block data in a list or spreadsheet, the steps are as follows:

- 1) Ensure block polygons supplied by the provider are 2000 currency.
- 2) If other currency, convert to 2000 currency before proceeding.
 - a. To do this, remove the trailing letter (a, b, etc.) from the block ID.
 - b. You will now have two blocks that equate to one block in the 2000 block geometry.
 - c. Delete duplicate block IDs, retaining the higher service tier in each case.
- 3) Prepare the block list in clean Excel format, removing all Excel-only formatting, merged cells, colors, borders, etc.
- 4) Import the spreadsheet into ArcMap®.
- 5) Right-click on the 2000 census block feature class in the layer list in ArcMap® and select **Joins and Relates>Join** from the dropdown menu. Join the census block list to the 2000 census blocks feature class using the block ID and export joined records in a new feature class. The **Join** dialog



BROADMAP
Beyond The Boundaries


box and process can be seen above in the **TIGER® Street Segments—List, Spreadsheet or GIS Data** subsection.

- 6) Follow the steps in **Census Blocks—GIS Data** below.


CENSUS BLOCKS—GIS DATA

In the event that the provider supplies census block GIS data, the steps are as follows:

- 1) Ensure that the blocks supplied by the provider are in the required data schema and are complete as far as required attribution.
 - a. If not, manually enter the required attribution or contact the provider to fill gaps.
- 2) If census block geometry is distributed throughout more than one county, then select **Data Management Tools>Generalization>Dissolve** in ArcToolbox® and dissolve based on County/Provider/TT/Speed Tier so that unique records are created for each unique combination.
 - a. The **Dissolve** dialog box is shown above in the **TIGER® Street Segments—List, Spreadsheet or GIS Data** section.
 - b. Two examples of undissolved census block polygons are shown below:



Undissolved census block polygons



Census block polygons dissolved by county

- 3) For each dissolved region use the **Editing** toolbar in ArcMap® to remove unnecessary slivers and other small holes.



BROADMAP
Beyond The Boundaries

- 4) In ArcToolbox®, select **Data Management Tools>General>Merge** and merge the processed polygons into a single layer.
- 5) The merged census blocks will need to have the subscriber's frn field added and populated.
- 6) In ArcCatalog®, create an empty feature class with the schema of the bb_cov feature class and load the GIS feature class either created above or supplied by the provider into it.
 - a. Right-click on the empty feature class, select **Load>Load Data** from the dropdown menu and navigate to the location of the service area feature class.
 - b. Click the **Add** button, then click **Next**.
 - c. Accept the defaults and click **Next**.
 - d. DO NOT attempt to map any fields, as shown below:

Simple Data Loader

For each target field, select the source field that should be loaded into it.

Target Field	Matching Source Field
ProvName [string]	<None>
DBAName [string]	<None>
FRN [int]	<None>
GeogUnit [string]	<None>
GeogUnitID [string]	<None>
TransTech [short int]	<None>
MaxAdvDown [short int]	<None>
MaxAdvUp [short int]	<None>
ARPU [float]	<None>
SWNomSpeed [float]	<None>


Reset

< Back Next > Cancel

- e. Click **Next**, then **Next** again, then **Finish**.
- 7) In ArcToolbox®, go to **Data Management Tools>General>Append**.
- 8) Append the formerly empty feature class to bb_cov, completing the dialog box, as shown below:



BROADMAP
Beyond The Boundaries



- 9) Leave the **Schema Type** as TEST.
- 10) Click **OK**.
- 11) In ArcMap®, open bb_cov for editing and manually input associated attribution, if necessary.

METADATA TRANSACTIONS

Following any updates or changes completed within the file geodatabase (fGDB) stored on the GIS-Analysts staging environment, the GIS-Analyst runs transactions to compare that fGDB with the one stored on the Core server to ensure metadata on all changes is recorded.

The steps taken to run transactions on the updated Core database are outlined below:

- 1) Open a command line window and run generateTransactions.py:
 - a. Usage: `generateTransactions.py [Core fGDB] [Staging Environment fGDB]`
 - b. Example of command line:
`<path>generateTransactions.py <path>ST_BB_POLY_SRV_AREAS.gdb <path>ST_BB_POLY_SRV_AREAS.gdb`
- 2) Shown below is an example of the output screen that will be displayed:



BROADMAP
Beyond The Boundaries

```

----- Collecting Transactions -----

Calculating rec_id field for BBCov_0_BB_POLY_TEMPLATE
value can not be 0 or less
Trouble creating the progress meter

Calculating rec_id field for BBCov_10_CenturyLink
%   10   20   30   40   50   60   70   80   90  100
----|----|----|----|----|----|----|----|----|----|    Goal = 8

Merging change: X:\BDIA_BB_GDBs\MS_BB_POLY_SRV_AREAS.gdb\AddPt
Calculating Transaction fields for AddPt
%   10   20   30   40   50   60   70   80   90  100
----|----|----|----|----|----|----|----|----|----|    Goal = 1
*****
X:\BDIA_BB_GDBs\MS_BB_POLY_SRV_AREAS.gdb\AddPt...changes is complete.

Your transaction FeatureClasses are in:
\\michigan\AllAccess\BDIA_BB_GDBs_HIST\MS_BB_POLY_SRV_AREAS_HIST.gdb
-----

elapsed time = 2994.4 seconds

```

- 3) After the process has completed, results can be found in the ST_BB_POLY_SRV_AREAS_HIST.gdb:
 - a. The transactions scripts records changes at a feature level.
 - b. Shown below is a screenshot supporting the directory structure of the historical fGDB.

Name	Type	Modified
BBCov_10_Nunn	File Geodatabase Feature Class	8/30/2010 8:57:53 AM
AddPt	File Geodatabase Feature Class	11/30/2010 4:49:46 PM
BBCov_80_ATT	File Geodatabase Feature Class	11/30/2010 4:37:35 PM
BBCov_80_Sprint	File Geodatabase Feature Class	8/30/2010 9:24:00 AM
BBCov_10_DuboisTelExchange	File Geodatabase Feature Class	8/30/2010 8:21:41 AM
BBCov_70_MobileNet	File Geodatabase Feature Class	8/30/2010 8:22:48 AM
BBCov_10_Sunflower	File Geodatabase Feature Class	8/30/2010 8:23:55 AM
BBCov_10_Qwest	File Geodatabase Feature Class	8/30/2010 8:25:11 AM
BBCov_30_XOComm	File Geodatabase Feature Class	8/30/2010 8:26:18 AM
BBCov_41_Comcast	File Geodatabase Feature Class	8/30/2010 8:27:24 AM
BBCov_20_XOComm	File Geodatabase Feature Class	8/30/2010 8:28:32 AM
BBCov_50_Rye	File Geodatabase Feature Class	8/30/2010 8:29:39 AM
BBCov_71_SECOM	File Geodatabase Feature Class	9/10/2010 10:59:47 AM
BBCov_50_Glenwood	File Geodatabase Feature Class	8/30/2010 8:32:01 AM
BBCov_10_Rico	File Geodatabase Feature Class	8/30/2010 8:33:21 AM
BBCov_71_SanIsabel	File Geodatabase Feature Class	8/30/2010 9:31:55 AM
BBCov_80_Verizon	File Geodatabase Feature Class	8/26/2010 2:33:20 PM
BBCov_10_Wiggins	File Geodatabase Feature Class	8/30/2010 8:37:43 AM
BBCov_10_PlainsCoop	File Geodatabase Feature Class	11/30/2010 4:35:50 PM
BBCov_70_Bijou	File Geodatabase Feature Class	11/30/2010 4:36:30 PM
BBCov_30_Covad	File Geodatabase Feature Class	9/10/2010 11:07:22 AM
BBCov_70_SouthPark	File Geodatabase Feature Class	8/30/2010 8:42:13 AM
BBCov_10_HaxtunTele	File Geodatabase Feature Class	8/30/2010 8:42:17 AM

- c. Attribution associated with each added/removed/changed feature is tracked, including the following additional columns appended to the end of each:



BROADMAP
Beyond The Boundaries

- (i.) Commit_by
 - (1) Records the GIS-Analyst who committed the changes to the historical fGDB.
 - (ii.) Commit_date
 - (1) Records the date and time stamp on which the changes were committed.
 - (iii.) Trans_type
 - (1) This field reflects the type of change recorded;
 - (2) Categorized by: Adds/Change/Deletes.
 - (iv.) New_values
 - (1) Records the new values when a change was completed on a feature. Example: Name or speed change.
- d. MD_Process also is transferred from the edited fGDB to the historical fGDB, which states the actions completed by the GIS-Analyst.

ArcCatalog - ArcView - M:\BDIA_BB_GDBs_HIST\CO_BB_POLY_SRV_AREAS_HIST.gdb\AddPt

File Edit View Go Tools Window Help

Location: M:\BDIA_BB_GDBs_HIST\CO_BB_POLY_SRV_AREAS_HIST.gdb\AddPt

Stylesheet: FGDC ESRI

md_address	md_process	commit_by	commit_date	trans_type	new_values
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5767]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5768]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5769]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5770]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5771]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5772]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5773]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5774]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5775]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5776]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5777]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5778]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5779]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5780]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5781]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5782]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5783]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5784]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5785]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5786]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5787]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5788]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5789]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5790]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5791]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5792]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5793]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5794]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5795]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5796]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5797]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5798]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5799]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5800]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5801]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5802]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5803]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5804]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5805]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5806]	
addBaseBBMetadataFields.py_v1.2. added Jab Mid Mile points back into db per critigen	cmabeey	8/24/2010 4:43:5	change	[5807]	

Record: 1 1 Show: All Selected Records (of 29424) Options

DATA PROCESSING

DATA PROCESSING OVERVIEW

The following subsections detail the steps and layout required to process the service provider data further to meet NTIA requirements:

- **Weighted Nominal Speed;**
- **Middle Mile;**
- **Broadband Coverage Template.**



BROADMAP
Beyond The Boundaries

WEIGHTED NOMINAL SPEED

The weighted nominal speed is populated in one of the following two ways: **subscriber data supplied by provider** or **value supplied by provider**.

SUBSCRIBER DATA SUPPLIED BY PROVIDER

Where the data provider supplies subscriber speed information, the following formula from the NOFA is used:

$$\frac{(\text{speed tier-1 in kbps} \times \text{no. of tier-1 subscribers}) + (\text{speed tier-2 in kbps} \times \text{no. of tier-2 subscribers}) + (\text{etc.})}{\text{Total average monthly subscribers}}$$

Data is initially broken up in the following order:

- 1) Stcty_fips;
- 2) Transmission technology type;
- 3) Subscriber tiers.

VALUE SUPPLIED BY PROVIDER

Some providers will supply their weighted nominal speed. In these cases, the data supplied will be populated instead of using the NOFA formula. These obtained or calculated values are used to update the service overview layer.

This can be done manually or by creating a table with the provider's FRN and average weighted speed and joining it to the service overview table in ArcMap®.

- 1) To join, right-click on the layer to join to and select **Joins and Relates>Join** from the dropdown menu.
- 2) Then navigate to the table to join to and select the join fields from the dropdown list.
- 3) Then open the source table (the table in ArcMap®) and right-click on the header of the **Average Weighted Speed** field and select **Calculate Field** from the dropdown menu.
- 4) Use the value of the average weighted speed from the joined table.

MIDDLE MILE

Middle mile information generally is provided in spreadsheet or text file format. The process is to take what is supplied by the provider and translate it into the required data schema.

- 1) If the data is supplied with address information, follow the process outlined above in **Subscriber Location—Address Data**.
- 2) If the data is supplied with associated XY coordinates, follow the process outlined above in **Subscriber Location—XY Data**.
- 3) Once the data is in GIS format, use the **Append (Data Management Tools>General>Append)** command in ArcToolbox® to append the data to the overall middle mile dataset.
- 4) Set the schema type to NO_TEST and use the Field Map to map the attribute fields from the source to the target dataset.



BROADMAP
Beyond The Boundaries

BROADBAND COVERAGE TEMPLATE

The table below lists descriptions of the fields within the bb_cov layer, which is the interim dataset used to create the final product deliverable.

NAME	ALIAS	DESCRIPTION
objectid	OBJECTID	Internal Object ID
shape	SHAPE	Internal Shape storage
prov_id	PROVIDER_ID	Unique numeric identifier for each provider
prov_name	PROVIDER_NAME	Unique name for each provider
dba_name	DOING_BUSINESS_AS	An alternative "Doing-Business-As" name for the provider
frn	FCC_REGISTRATION_NUMBER	Provider FCC Registration Number
bbcov_name	BBCOV_NAME	BroadMap Broadband Coverage name
trans_code	TRANSMISSION_CODE	Unique code for the transmission technology type described by this layer
trans_name	TRANSMISSION_NAME	Name for the transmissions technology type
trans_desc	TRANSMISSION_DESC	Description for the transmissions technology type
spect_code	SPECTRUM_CODE	Unique code for the spectrum [WIRELESS ONLY]
spect_name	SPECTRUM_NAME	Name for the spectrum [WIRELESS ONLY]
spect_desc	SPECTRUM_DESC	Description for the spectrum [WIRELESS ONLY]
mad_dwn_t	MAX_AD_DOWN_TIER	Maximum advertised downstream speed available within given area (speed tier)
mad_up_t	MAX_AD_UP_TIER	Maximum advertised upstream speed available within given area (speed tier)
typ_dwn_t	TYPICAL_DOWN_TIER	Typical downstream speed available within given area (speed tier)
typ_up_t	TYPICAL_UP_TIER	Typical upstream speed available within given area (speed tier)
mad_dwn_k	MAX_AD_DOWN_KBPS	Maximum advertised downstream speed available within given area (kbps)
mad_up_k	MAX_AD_UP_KBPS	Maximum advertised upstream speed available within given area (kbps)
typ_dwn_k	TYPICAL_DOWN_KBPS	Typical downstream speed available within given area (kbps)
typ_up_k	TYPICAL_UP_KBPS	Typical upstream speed available within given area (kbps)
subs	SUBSCRIBERS	Total average monthly subscribers for this provider for this technology for this coverage polygon
md_geom	MD_GEOMETRY	Metadata: Comma separated list of source ids from which the polygon extent was produced
md_exists	MD_EXISTS	Metadata: Comma-separated list of source ids used in understanding and editing the provider data for this polygon



BROADMAP
Beyond The Boundaries

NAME	ALIAS	DESCRIPTION
md_who	MD_WHO	Metadata: Name of the editor who last edited this feature at the time in md_when
md_when	MD_WHEN	Metadata: Date/time that this feature was last edited
md_process	MD_PROCESS	Metadata: Comma-separated list of processes used to create and/or modify this layer
stcty_fips	STATE_COUNTY_FIPS	State/County FIPS code
rec_id	RECORD_ID	Compound Key formed from STCTY_FIPS+" "+Provider_ID+" "+Trans_Code+" "+BBCov_Name
st_area	ST_AREA(SHAPE)	Area in square decimal degrees
st_length	ST_LENGTH(SHAPE)	Length in decimal degrees
Provider_Type	Type of Provider	Has Subtype (1:Broadband provider as described in the NOFA,2:Reseller,3:Unknown), default value=1 (New 04/11 Model)

VERIFICATION AND VALIDATION

PROVIDER VALIDATION—PROVIDER PORTAL/PDF MAP REVIEW

Following the collection and aggregation of provider data, the aggregated data is validated by the provider to ensure it is an accurate representation of their coverage area and supporting broadband information.

- This validation is completed through the Provider Portal web application, which is a secure interactive map that displays the provider's coverage areas and allows the provider to validate, submit feedback or request changes.
 - If changes are requested, then the features on the portal are updated and an automatic request is sent to the provider to complete the validation process.
- Providers that did not use the Provider Portal are asked to validate a PDF map displaying their coverage area(s). This is accomplished via e-mail notification.

PROVIDER VERIFICATION—THIRD PARTY SOURCE REVIEW

After the provider has validated its coverage areas, a third-party source comparison and analysis is performed.

- Where anomalies or discrepancies are identified, a "SCAN" point is dropped and descriptive comments are applied to be reviewed later with the provider.
- During the provider review, the map is displayed along with the "SCAN" points and potential refinement is completed based on input from the provider.

The table below shows third-party sources used:

THIRD-PARTY SOURCE NAME	SOURCE TYPE	VERIFICATION TYPE
InfoUSA	Consumer and Business Listings	Community Anchor Institutions; Can also be used for demographic information supporting the State websites.
Pitney Bowes (PBBI)	Exchange Info Plus (Central Office Locations)	Exchange datasets are used to verify the following Transmission Technologies (TT): Asymmetric xDSL (10), Symmetric xDSL (20), Other Copper Wireline (30), and Optical Carrier/Fiber to the End User (50).



BROADMAP
Beyond The Boundaries

THIRD-PARTY SOURCE NAME	SOURCE TYPE	VERIFICATION TYPE
Media Prints	Cable Boundaries	Used to verify the following TT: Cable Modem—DOCSIS 3.0 (40) and Cable Modem—Other (41).
American Roamer	Wireless Coverage Patterns (EVDO, GPRS, WISP, HSPA)	Used to verify the following TT: Terrestrial Fixed Wireless—Unlicensed (70), Terrestrial Fixed Wireless—Licensed (71) and Terrestrial Mobile Wireless (80).
ComSearch	Wireless Spectrum Holdings and Tower Data	Used to verify the following TT: Terrestrial Fixed Wireless—Unlicensed (70), Terrestrial Fixed Wireless—Licensed (71) and Terrestrial Mobile Wireless (80).

ASSIGNING CONFIDENCE VALUES

All findings and results from the abovementioned **validation and verification activities**, plus internal peer quality reviews, are captured and tracked in a **Validation table** (see example on the following page) and form the basis of the confidence value assigned for each provider and then each technology.

CONFIDENCE VALUE	DESCRIPTION
0	Coverage area has not been reviewed.
10	Extremely Low: Single Source QC.
20	Very Low: Needs additional validation\verification. Coverage has not been validated by provider and is not found in third-party sources.
30	Low: Even with validation\verification, coverage still is suspect.
40	Presentable: Meets NTIA/State's standards, broadband attribution (technology vs. speeds) is questionable and needs to be validated by provider.
50	Acceptable: Meets NTIA/State's standards, display is generalized or doesn't align completely with technology capability. Okay for shipment, but requires further review.
60	Moderate: Meets NTIA/State's standards and is representative of the Technology Type (TT).
70	High: Accurate representation of coverage based upon TT and aligns with a third-party source.
80	Very High: Multiple validation\verification with most third-party sources.
90	Extremely High: Multiple validation\verification sources.
100	Perfect: Multiple validation\verification sources, with complete alignment with sources and ground truth verification activities.



BROADMAP
Beyond The Boundaries



The **Validation table** is maintained as updates or changes occur for each provider, down to technology type, with the overall goal to improve the confidence values and overall map representation. An example of the Validation table is shown below:

OBJECT ID	OBJECT	CONFIDENCE CODE	PROVIDER ID	PEER GC	PROVIDER GC	THIRD PARTY VERIFICATION	THIRD PARTY ID	COMMENTS
1	BBCCV_10_Axinn	40	771	11/4/2010	9/27/2011	11/4/2010	3070	Axinn doesn't exist in Pinyoweb's exchange data. Geometry and attribution are ok.
2	BBCCV_10_BeauteTaco	80	850	10/10/2010	3/30/2011	6/7/2010	2010	BeauteTaco #10 boundary has general shape of overlapping pinyoweb's exchange boundary but not a perfect 1:1. 030911 confidence raised.
3	BBCCV_10_CanbyTelcom	80	790	10/10/2010	9/27/2011	6/7/2010	2010	Canby Telcom boundary is roughly the shape of two exchanges but not 1:1.
4	BBCCV_10_CascadiaCell	70	3000	11/4/2010		11/4/2010	3070	CascadiaCell still needs provider validation. This block exists in Pinyoweb's exchange boundaries. Areas where they do not correspond to CenturyLink BBCCV overlays Pinyoweb's exchange boundaries in some places, and not in others. Geometry and attribution representative of CenturyLink overlays with Pinyoweb's exchange boundary. Visions doesn't scan it was dropped. Geometry and attribution are ok.
5	BBCCV_10_CenturyLink	70	710	11/4/2010	9/23/2010	11/4/2010	3070	CenturyLink BBCCV overlays Pinyoweb's exchange boundaries in some places, and not in others. Geometry and attribution representative of CenturyLink overlays with Pinyoweb's exchange boundary. Visions doesn't scan it was dropped. Geometry and attribution are ok.
6	BBCCV_10_CulbertTel	80	713	11/4/2010	9/16/2010	11/4/2010	3070	CulbertTel overlays with Pinyoweb's exchange boundary. Visions doesn't scan it was dropped. Geometry and attribution are ok.
7	BBCCV_10_Covad	80	717	11/4/2010	9/23/2010	11/4/2010	3070	Covad does not exist in Pinyoweb's exchange boundaries dataset. Geometry and attribution are ok.
8	BBCCV_10_DataVision	30	787	11/4/2010		11/4/2010	3070	SBI needs Provider GC. DataVision does not exist in Pinyoweb's exchange boundaries dataset. Geometry and attribution are ok.
9	BBCCV_10_EasternOregonTelcom	80	889	11/4/2010	9/20/2010	11/4/2010	3070	Eastern Oregon Telcom does not exist in Pinyoweb's exchange boundaries dataset. Geometry and attribution are ok.
10	BBCCV_10_Frontier	70	784	11/4/2010	9/16/2010	11/4/2010	3070	Frontier is partially overlaid by Pinyoweb's exchange boundaries. Areas of difference have scan pits dropped. Geometry and attribution are ok.
11	BBCCV_10_Gervase	90	787	10/10/2010	9/22/2010	6/7/2010	2010	Map portion of boundary is general shape of corresponding exchange boundary.
12	BBCCV_10_Hale	70	726	11/4/2010	9/22/2010	11/4/2010	3070	Hale BBCCV resides mostly within Pinyoweb's exchange boundary of the same name. Scan Pits dropped where different. Geometry and attribution are ok.
13	BBCCV_10_Integra	30	790	10/10/2010	9/27/2010	6/7/2010	2010	Many BBCCV poly's roughly align to 3rd party exchange boundaries in areas.
14	BBCCV_10_Kodiakville	80	732	11/5/2010	9/27/2010	11/5/2010	3070	BBCCV Kodiakville resides wholly within the Kodiakville Exchange boundary in pinyoweb's dataset which is attributed as Verizon NW.
15	BBCCV_10_Kodiakville	90	734	10/10/2010	9/30/2010	6/7/2010	2010	Northern part of BBCCV roughly aligns to northern part of 3rd party exchange boundary.
16	BBCCV_10_Kodiakville	70	1100	10/10/2010	9/17/2010	6/7/2010	2010	Coverage area larger than overlapping exchange boundary but overall shape roughly resembles the exchange boundary.
17	BBCCV_10_Kodiakville	80	730	10/10/2010	9/20/2010	6/7/2010	2010	3rd party exchange boundary very similar to BBCCV.
18	BBCCV_10_Kodiakville	80	737	10/10/2010	9/30/2010	6/7/2010	2010	3rd party exchange boundary very similar to BBCCV.
19	BBCCV_10_Kodiakville	80	790	10/10/2010	9/30/2010	6/7/2010	2010	Large portion of BBCCV roughly aligns to underlying 3rd party exchange but not all.
20	BBCCV_10_Kodiakville	80	730	10/10/2010	9/30/2010	6/7/2010	2010	BBCCV resides mostly within the Pinyoweb's exchange boundary. Geometry is suspect. Attribution is ok. Provider validated via portal.
21	BBCCV_10_Kodiakville	80	730	11/5/2010	9/14/2010	11/5/2010	3070	Very generalized block partially overlapping Pinyoweb's exchange boundaries. Geometry is suspect. Attribution is ok.
22	BBCCV_10_Kodiakville	80	1012	11/5/2010	9/17/2010	11/5/2010	3070	Peoples BBCCV mostly resides within Pinyoweb's Exchange boundary of same name. Scan Pits dropped where differ. Geometry and Attribution are ok.
23	BBCCV_10_Kodiakville	70	787	10/10/2010	9/17/2010	6/7/2010	2010	BBCCV area has general shape as underlying exchange boundary here. Coverage areas based off of CenturyLink. 03/11/11 Provider valid.
24	BBCCV_10_Kodiakville	80	740	11/5/2010	9/20/2010	11/5/2010	3070	BBCCV Pioneer resides mostly within Pinyoweb's exchange boundaries of same name. Scan Pits dropped where differ. Geometry and attribution are ok.
25	BBCCV_10_Kodiakville	80	1102	11/5/2010	9/20/2010	11/5/2010	3070	BBCCV Pioneer resides mostly within Pinyoweb's exchange boundaries of same name. Scan Pits dropped where differ. Geometry and attribution are ok.
26	BBCCV_10_Kodiakville	80	1012	11/5/2010	9/20/2010	11/5/2010	3070	BBCCV Pioneer resides mostly within Pinyoweb's exchange boundaries of same name. Scan Pits dropped where differ. Geometry and attribution are ok.
27	BBCCV_10_Kodiakville	80	740	10/10/2010	9/10/2010	6/7/2010	2010	BBCCV Pioneer resides mostly within Pinyoweb's exchange boundaries of same name. Scan Pits dropped where differ. Geometry and attribution are ok.
28	BBCCV_10_Kodiakville	80	873	11/5/2010	9/17/2010	11/5/2010	3070	3rd party exchange boundary very similar to BBCCV.
29	BBCCV_10_Kodiakville	80	880	10/10/2010	9/17/2010	6/7/2010	2010	BBCCV for city of Sandy does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
30	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	3rd party exchange boundary roughly aligns to BBCCV in the area 03/11/11 Provider validated coverage confidence high.
31	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
32	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
33	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
34	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
35	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
36	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
37	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
38	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
39	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
40	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
41	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
42	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
43	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
44	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
45	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.
46	BBCCV_10_Kodiakville	80	1010	11/5/2010	9/17/2010	11/5/2010	3070	BBCCV for SCS does not exist in Pinyoweb's exchange dataset. Geometry and attribution are good for TT.

COMMUNITY ANCHOR INSTITUTION (CAI) DATA

DATA COLLECTION

The CAI data was initially collected from the State to create the baseline inventory. All location information and broadband coverage data supplied also was ingested into the data deliverable. Additional collection of CAI information was done via data mining and/or web scraping to build out the inventory further. For example: Collection of additional CAIs and location information.

The State-agency-provided CAI inventory was comprehensive but the challenge is collecting broadband related data: service provider(s), technology and speed data for each CAI. Availability of the CAI portal has not significantly increased submission of this data. Additional promotion to CAIs to use the CAI portal will be needed to increase this data for subsequent deliverables.

INSTITUTION DATA

Institution data is obtained from a variety of sources and almost always provided in Excel spreadsheet format. The general process for incorporating this data is as follows:

- 1) If the data is provided in Excel or some similar format:
 - a. Clean and standardize the Excel spreadsheet, removing any cell formats, merged cells, etc.
 - b. Standardize the address format as defined in the staging CAI database.
 - c. If the spreadsheet includes X and Y values, such as latitude and longitude, use the **Add XY Data** tool in ArcMap® to create a spatial data layer.
 - d. If there are only addresses, then follow the geocoding steps outlined above to create spatial data points for each of the institutions.
 - i.) Institutions that do not geocode based on the TIGER® 2009 dataset will have to be located manually using Google Maps, Google Earth or some other information source.
- 2) If the CAI source data is in GIS format, add the Latitude and Longitude fields and use the **Calculate Geometry** tool to populate them, using the WGS 84 coordinate system.
- 3) Using ArcCatalog®, load the new data into the staging CAI database.



BROADMAP
Beyond The Boundaries

- 4) This database is ready for the makeDeliverable.py script to process the information into the final State and NTIA deliverables.

COMMUNITY ANCHOR INSTITUTION (CAI) PORTAL UPDATES

A web application has been released to allow for further data collection and validation of anchor institution location information, broadband coverage and speed test data. Information collected from the CAI Portal is then ingested into the overall inventory and will be compared later against the provider coverage areas mapped to locate any potential discrepancies.

PRODUCT EXTRACT

PYTHON SCRIPTS

The following subsections make use of Python scripts. In general, to use a Python script you must have Python installed on your computer. To download the latest version of Python, go to <http://www.python.org/download/> and download the latest stable version. As of August 2010, this was version 2.7. Once this is installed, the general way to run a script is to type the following at a command prompt: C:\Python27\python.exe C:\<location of script>. Many of the scripts provided have environment variables that must be set before they can be run.

The Python code for BroadMap's product extract has been incorporated into a Hudson CI System, which is detailed in the [Process Operation and Monitoring](#) section of this document. This was a process improvement activity so that all processes can be monitored, controlled and will contain historical tracking on each process.

PRODUCT EXTRACT PROCESS

NOTE:

Specific Python scripts are called out in **red** font in the subsections below.

The MapConnect™ product extract process, **makeDeliverable.py**, uses the BB_Cov and BROADMAP_POINTS interim datasets to create the following layers according to the current specifications:

- BB_Service_Road_Segment
 - This layer contains all broadband services associated with specific street segments for census 2000 blocks larger in area than two square miles.
- BB_ServiceCensusBlock
 - Contains all broadband services associated with census blocks of no greater than two square miles.
- BB_Service_Wireless
 - This layer contains all wireless services not associated with specific addresses.
- BB_ServiceOverview
 - This layer contains subscriber-weighted nominal speed for each provider's service area at a county level and is meant to act as a summarized view.
- BB_ConnectionPoint_MiddleMile
 - This layer contains middle-mile and backbone interconnection points.
- BB_Service_CAIInstitutions
 - Broadband Service at Community Anchor Institutions (CAI).



BROADMAP
Beyond The Boundaries

- Community Anchor Institutions consist of schools, libraries, medical and healthcare providers, public safety entities, community colleges and other institutions of higher education as well as other community support organizations and entities.

Because of a NTIA model change for the October 2010 data deliverable, an addition to this code was created to support both models in case a comparison is later desired or a request is made to revert to the original model. This script name is **bdia2ntia.py** and creates the following layers in addition to the layers mentioned above, rolled up to NATL_Broadband_Map.

- BB_ConnectionPoint_LastMile
 - This layer contains last mile infrastructure points, which is populated only if data cannot be provided at a more granular level.
- BB_Service_Address
 - Represents broadband availability for service address points. Address Point availability refers to those individual addresses at which each facilities-based provider of broadband service can provide broadband services of minimal characteristics within 7-10 business days.
- State_Boundary
 - State boundary supporting topological validation of point feature classes.
- NATL_Broadband_Topology
 - Supports basic topology quality checking. Example: No CAIs or Middle Mile points outside of the State boundary.

The following process flow provides a view of how the Core fGDB is extrapolated to the NTIA final deliverable via the makeDeliverable.py script. Following that, the bdia2ntia.py script is run, which limits what is placed in the final layers based on the NTIA modeling standards.

The product scripts and supporting extract were originally created separately per request, in case data model comparisons were to be completed.

PRODUCT STATISTICS

Following the completion of a product extract, the product statistics script (**BDIA_ReleaseNotesStats.py**) extracts the following information supporting that product deliverable.

- Provider Statistics:
 - Collects all provider information, listing by Provider Name.
 - Provides output of FRN.
 - Counts the number of features supported within the following layers:
 - Census Block;
 - Street Segment;
 - Max Upstream;
 - Wireless Services;
 - Infrastructure Points.
 - These updates were made to support the Data Package required to accompany every NTIA product deliverable.
- Community Anchor Institution (CAI) Statistics:
 - Breaks down CAI to the eight categories:
 - 1: School: K through 12;
 - 2: Library;
 - 3: Medical/Healthcare;
 - 4: Public Safety;
 - 5: University/College;
 - 6: Other Government;



BROADMAPSM
Beyond The Boundaries

- 7: Other Community non-government;
- None: Unknown Category. In cases where this occurs, further investigation is completed prior to product shipment to ensure all CAIs are categorized accurately.
- Reports out the following counts:
 - Total CAIs within that category;
 - Total CAIs that contain partial BB coverage. Contains any of the following information for a given CAI: BB Subscriber, Transmission Technology, Speed Down Speed Up;
 - Total CAIs that contain full BB coverage. Contains all of the abovementioned BB information for a given CAI.

The output of this script is two CSV files: AnchorInstitutions.csv and Providers.csv. These files then can be inspected to ensure that there are the expected number of CAIs and providers for every release.

QUALITY ASSURANCE

Quality assurance is supported manually and algorithmically on the interim data, BB_Cov file geodatabase and on the final product. For scheduled product releases, a test product extract and subsequent manual and algorithmic QC run is completed along with a release review. The product specifications, project status reports and previous product release notes are used as references throughout this review.

The following parameters are tested using the methodology listed below each:

- Product Deliverable Format:
 - Correct names and format of data deliverables.
 - **BDIA_QC_SUITES** (please see below for details).
 - Correct Projections/Datum.
 - Manual interaction with product.
 - Metadata Present and Correct.
 - Manual interaction with product.
- Table Structure:
 - All required tables included.
 - **BDIA_QC_SUITES**.
 - Extraneous tables identified.
 - **BDIA_QC_SUITES**.
- Field Structure:
 - All fields included.
 - **BDIA_QC_SUITES**.
 - Extraneous fields identified.
 - **BDIA_QC_SUITES**.
 - Correct field names, types and widths.
 - **BDIA_QC_SUITES**.
- Field Domains:
 - Values in all tables are constrained to the specified values specified:
 - This action is accomplished via **BDIA_QC_SUITES** and manual review of the product;
 - This tends to identify project completeness issues as fields with a null value are identified.
- Geometric Representation:
 - Identify if all layers have the correct geometric representation:
 - Manual review of the BB_ServiceOverview layer;
 - Dependent on NTIA and client requirements.
- Geographic Extent:
 - Product includes the necessary Geography associated with Product?
 - Manual Review—ArcGIS®.



BROADMAP
Beyond The Boundaries

- Is there extraneous geography included in Product?
 - Manual Review—ArcGIS®.
- Completeness:
 - Products contain the expected amount of data?
 - Manual review of product statistics relative to weekly State reports and defined expectations.
- Accuracy:
 - Product meets the stated accuracy requirements for the deliverable?
 - Sampling procedure to manually review source material to resulting product;
 - Provider Validation;
 - Verification using Third-Party Data;
 - Verification against reality, where applicable.
- Data Regression:
 - Any unexplainable data loss or change?
 - This action is accomplished by comparing results within product statistics script ([BDIA_ReleaseNotesStats.py](#)) from previous releases, as well as manual review of the product.
- Confidentiality:
 - Any unauthorized confidential information included in the delivery?
 - Review of NDAs and delivery expectations.
- Prior Issues Resolved:
 - Have expected internal issues been resolved?
 - Manual review of data against previous product release notes.
 - Have agreed-upon customer issues been resolved?
 - Manual review of data against previous product release notes, status report and client feedback.
- Delivery Medium:
 - Has the product medium been verified?
 - Manual review.
 - All files present.
 - Manual review of SFTP site to ensure all files are copied correctly, including file/directory size.
 - Correct location.
 - Manual review—confirmation of SFTP link, username and password.

QC SUITE

The **BDIA_QC_SUITES** consists of four main types of scripts supporting the overall QC process. These scripts are all run in concert and are called from the **test_runner** script and the **test_BDIAProductGDB** script.

CONFIGURATION

These scripts establish the configuration for the **test_BDIAProductGDB** script, which is the core of the QC Suite.

update_test_config
active_config
config_PROCESS01_automated
config_PROCESS01_manual
set_active_config

LIBRARIES

These scripts provide additional functionality that is called from with the **test_BDIAProductGDB** script.

bb_unittest_fixture
bbcov_structure



BROADMAP
Beyond The Boundaries

BC_XmlWriter
file_folder
search_and_replace
unittest_fixture
validate_BB_DB
validate_BB_GDB
xmlrunner_gui

QC SUITE

This is the core script for performing automated QA/QC on the interim and final data deliverables.

test_BDIAProductGDB

OTHER

These scripts perform other functions detailed below:

test_runner—this is the main script that runs all the other QC scripts and imports all the necessary scripts and libraries.

which_build—this determines the current build and passes information to the configuration scripts.

PROCESS OPERATION AND MONITORING

Product Extract, makeDeliverable.py and bdia2ntia.py, is run within BroadMap using a platform called Hudson that has been enhanced to support BDIA product extraction, process monitoring, as well as product validation. The same platform can be planned for implementation for the State, if desired.

Below are examples of the product create, product validation, product statistics and monitoring processes that are managed within the BroadMap Hudson CI-System. All of the abovementioned Python scripts, with the exception of metadata transactions script, are run via this system.

BDIA PRODUCT CREATE

Below is an example of the main page where the type of product build can be selected.

The screenshot displays the Hudson CI System interface. On the left, there is a sidebar with navigation links: New Job, Manage Hudson, People, and Build History. The main area shows the 'Build Queue' with a table of jobs. The table has columns for Job Name, Last Success, Last Failure, and Last Duration. The jobs listed are: BDIA_Build, BDIA_Product_Validation_AS, BDIA_Product_Validation_CNHI, and BDIA_Product_Validation_CO. The interface also includes a search bar and a 'ENABLE AUTO REFRESH' button.

Job Name	Last Success	Last Failure	Last Duration
BDIA_Build	12 hr (#192)	N/A	12 sec
BDIA_Product_Validation_AS	2 mo 10 days (#137)	N/A	8 min 10 sec
BDIA_Product_Validation_CNHI	3 mo 22 days (#81)	3 mo 23 days (#80)	2 min 16 sec
BDIA_Product_Validation_CO	13 days (#271)	N/A	37 min



BROADMAP
Beyond The Boundaries

Selecting based on the type of process that will be initiated is shown below:

Hudson
Hudson > BDIA_ProductCreate > BDIA_ProductCreate

[Back to Dashboard](#)

[Status](#)
[Changes](#)
[Workspace](#)
[Build Now](#)
[Delete Project](#)
[Configure](#)

Project BDIA_ProductCreate
OR on Alaska

[Workspace](#)

[Last Successful Artifacts](#)

- [bdia2ntia.log](#)
- [makeDeliverable.log](#)
- [robocopy.log](#)

[Recent Changes](#)

Build History (trend)

#	Time	Size
#123	Dec 9, 2010 12:30:00 PM	186KB
Running for provider portal update		
#122	Dec 9, 2010 9:53:37 AM	179KB
Running for provider portal update - Test will rerun when Midco is complete		
#121	Dec 7, 2010 6:09:02 PM	46KB
SD build for portal test		
#119	Dec 1, 2010 12:41:51 AM	125KB
CO Monthly Deliverable w/ Crit Feedback - Round 2		
#118	Nov 30, 2010 4:58:46 PM	50KB
CO Monthly Deliverable w/ Crit Feedback		

Permalinks

- [Last build \(#123\), 4 days 23 hr ago](#)
- [Last stable build \(#123\), 4 days 23 hr ago](#)
- [Last successful build \(#123\), 4 days 23 hr ago](#)
- [Last failed build \(#121\), 6 days 18 hr ago](#)
- [Last unsuccessful build \(#121\), 6 days 18 hr ago](#)

Hudson
Hudson > BDIA_ProductCreate > BDIA_ProductCreate

[Back to Dashboard](#)

[Status](#)
[Changes](#)
[Workspace](#)
[Build Now](#)
[Delete Project](#)
[Configure](#)

Project BDIA_ProductCreate
This build requires parameters:

State: State or Territory to Process

[Build](#)

[Recent Changes](#)

The Console Output can be reviewed to see the progress of product create. Following the completion of each product creation process, an e-mail notification is automatically sent to the team.

Hudson
Hudson > BDIA_ProductCreate > BDIA_ProductCreate > #117

[Back to Project](#)
[Status](#)
[Changes](#)
[Console Output](#)
[Parameters](#)
[Test this build](#)
[Download build view](#)
[Previous Build](#)
[Next Build](#)

Console Output

```
Started by user anonymous
Building on master
Updating http://www.Product/Python/BDIA_ProductCreate/trunk/asp
A
makeDeliverable.py
generateCreateFunctions.py
At revision 2028
WARNING: clock of the subversion server appears to be out of sync. This can result in inconsistent check out behavior.
(workspace) % cmd /c call C:\Users\anderson\AppData\Local\Temp\hudson3085558419495832.bat
D:\hudson\jobs\BDIA_ProductCreate\workspace\robocopy.log
Log File : D:\hudson\jobs\BDIA_ProductCreate\workspace\robocopy.log
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 16 echo ROBOCOPY RETURN CODE 3 ***FATAL ERROR*** & goto ERROR
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 15 echo ROBOCOPY RETURN CODE 3 FAIL MISM XTRA COPY & goto ERROR
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 14 echo ROBOCOPY RETURN CODE 3 FAIL MISM XTRA & goto ERROR
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 13 echo ROBOCOPY RETURN CODE 3 FAIL MISM COPY & goto ERROR
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 12 echo ROBOCOPY RETURN CODE 3 FAIL MISM & goto ERROR
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 11 echo ROBOCOPY RETURN CODE 3 FAIL XTRA COPY & goto ERROR
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 10 echo ROBOCOPY RETURN CODE 3 FAIL XTRA & goto ERROR
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 9 echo ROBOCOPY RETURN CODE 3 FAIL COPY & goto ERROR
D:\hudson\jobs\BDIA_ProductCreate\workspace>if errorlevel 8 echo ROBOCOPY RETURN CODE 3 FAIL & goto ERROR
```

All processes run via the BroadMap Hudson CI-System are stored for historical reporting. Each process can be reviewed, including the Console Output and Build Artifacts from that run.



BROADMAP
Beyond The Boundaries

Hudson

Hudson > BDIA Product Create > BDIA_ProductCreate > #161

[Back to Project](#)

[Status](#)

[Changes](#)

[Console Output](#)

[Parameters](#)

[Tag this build](#)

[Downstream build view](#)

[Previous Build](#)

[Next Build](#)

Build #161 (Mar 28, 2011 9:44:40 PM)

OR Pre-Release Build



[Build Artifacts](#)

- [bdia2ntia.log](#)
- [makeDeliverable.log](#)
- [robocopy.log](#)



Revision: 3099
No changes.



Started by user [anonymous](#)

[search](#)

[ENABLE AUTO REFRESH](#)

[Delete this build](#)

Started 1 day 1 hr ago
Took [3 hr 31 min](#) on [Alaska](#)

[edit description](#)






BROADMAP
Beyond The Boundaries

PRODUCT VALIDATION AND STATISTICS


Once the product creation process is complete, Product Validation and Statistics are then initiated. These support the **BDIA_ReleaseNotesStats.py** script and the **BDIA_QC_SUITES** scripts detailed above.

All statistics and reports are stored for historical review with the capability to place violation criticality on each quality control check, allowing the identification of errors because of project status/completeness verses project correctness. Example: Typical Speeds populated.

Below is an example of the report provided based on various control points running over a specified period:



Similar to the Product Create process, all results from the process are maintained:





BROADMAP
Beyond The Boundaries

Results are then reviewed manually to ensure no errors reported are critical or in violation of the NTIA data model or project completion statements. Any errors of concern are communicated ahead of product delivery and included within the product release notes. Further detail on the Hudson-CI System environment can be found by navigating to the following link:

<http://wiki.hudson-ci.org/display/HUDSON/Meet+Hudson>

The screenshot shows the Hudson CI web interface. On the left is a sidebar with navigation links: Back to Dashboard, Status, Changes, Workspace, Build Now, Delete Project, Configure, and Plots. The main content area is titled 'Hudson' and shows details for the 'BODIA_Product_Validation_CO' project. It includes a 'Build History' table with columns for build number, timestamp, and size. The table lists builds from #260 to #280. To the right of the build history is a 'Configuration' section for the 'String Parameter' 'TestMethodPrefix'. It shows the default value as 'BODIA_STRUCTURE' and a description. Below this is another 'String Parameter' section for 'GDBLocation', showing the default value as '//alaska/ReleaseCandidates/CO_20101117-1947' and a description as 'Parent path for the release candidate GDB'.

PRODUCT EXTRACT DATA DELIVERY

Product delivery for MapConnect™ Broadband is handled two ways, depending on client requirements:

- 1) State Submittal:
 - a. Data is submitted via SFTP site;
 - b. Product Release Notes and QC Test Report accompany the delivery.
- 2) NTIA Submittal:
 - a. Directions for using the NTIA State Broadband Data file submission tool:
 - (i.) Go to the following website: <https://esupport.fcc.gov/statedata>;
 - (ii.) Enter your **username** and **password** as provided to you from the NTIA program administrator;

The screenshot shows the 'FCC SUPPORT CENTER' header and the 'Broadband State Data Management Tool' title. Below the title is a 'Login' section with a form. The form has two input fields: 'Username:' with the value 'fcc' and 'Password:' with a masked password '*****'. There is a 'LOGIN' button below the password field.

- (iii.) Click in **Upload a file** field;
- (iv.) Browse to local file for submission using the **Browse** button. Select file, then select **ATTACH FILE**. See example below.



BROADMAPSM
Beyond The Boundaries

- (v.) **Logout/Receipt** using the **Logout** button in the top right of the screen;
- (vi.) A receipt of submission is e-mailed to username e-mail address.